



mlBibTeX: Reporting the Experience

Jean-Michel Hufflen

► To cite this version:

| Jean-Michel Hufflen. mlBibTeX: Reporting the Experience. TUGB, 2007, pp.157–162. hal-00644467

HAL Id: hal-00644467

<https://hal.science/hal-00644467>

Submitted on 24 Nov 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

MlBIBTeX: Reporting the Experience*

Jean-Michel HUFFLEN
LIFC (EA CNRS 4157)
University of Franche-Comté
16, route de Gray
25030 BESANÇON CEDEX
FRANCE
hufflen@lifc.univ-fcomte.fr
<http://lifc.univ-fcomte.fr/~hufflen>

Abstract

This article reports how the different steps of the MlBIBTeX project were conducted until the first public release. We particularly focus on the problems raised by reimplementing a program (BIBTeX) that came out in the 1980's. Since this time, implementation techniques have evolved, new requirements have appeared, as well as new programs within TeX's galaxy. Our choices are explained and discussed.

Keywords TeX, LATEX, BIBTeX, reimplementation, reverse engineering, implementation language, program update.

Streszczenie

Artykuł omawia realizację poszczególnych kroków przedsięwzięcia MlBIBTeX, w czasie do przedstawienia pierwszej publicznej wersji. W szczególności skupiamy się na problemach powstających przy reimplementacji programu (BIBTeX), powstało w latach 80 zeszłego wieku. Od tego czasu rozwinęły się techniki implementacyjne, powstały nowe wymagania oraz nowe programy w świecie TeX-owym. Przedstawiamy i dyskutujemy dokonane wybory.

Słowa kluczowe TeX, LATEX, BIBTeX, reimplementacja, *reverse engineering*, język implementacji, aktualizacja programu.

0 Introduction

In 2003, TeX's 25th anniversary was celebrated at the TUG¹ conference, held at Hawaii [1]. LATEX [28] and BIBTeX [35]—the bibliography processor usually associated with the LATEX word processor—are more recent, since they came out in the 1980's, shortly after TeX. All are still widely used, such longevity being exceptional for software. However, these programs are quite ageing. Of course, recent versions have incorporated many features absent from the first versions, what proves the robustness of these systems. Nevertheless, they present some limitations due to the original conception, and a major reimplementation may be needed to integrate some modern requirements. In addition, interactive word processors made important progress and are serious rivals, even if they do not yield typesetting of such professional quality. That is why some

projects aim to provide new programs, based on TeX & Co.'s ideas.² A first representative example is the LATEX 3 project [32], a second is NTS [27].

MlBIBTeX—for ‘MultiLingual BIBTeX’—belongs to such projects. Let us recall that this program aims to be a ‘better BIBTeX’, especially about multilingual features. For a end-user, MlBIBTeX behaves exactly like ‘classical’ BIBTeX: it searches bibliography data base (.bib) files for citation keys used throughout a document and arranges the references found into a .bbl file suitable for LATEX, w.r.t. a bibliography style. MlBIBTeX is written in Scheme,³ it uses XML⁴ as a central format: when entries of .bib

² Concerning TeX, an additional point is that TeX's development has been frozen by its author, Donald E. Knuth [26]. If incorporating new ideas to a ‘new TeX’ leads to a major reimplementation, the resulting program must be named differently.

³ The version used is described in [24].

⁴ EXtensible Markup Language. Readers interested in an introductory book to this formalism can consult [37].

* Title in Polish: *MlBIBTeX: raport z doświadczeń*.

¹ TeX Users Group.

files are parsed, they result in an XML tree. Bibliography styles taking advantage as far as possible of MIBIBTEX's new features are written using `nbst`,⁵ a variant of XSLT⁶ described in [15]. The `bst` language [34], based on handling a stack and used for writing bibliography styles of BIBTEX, can be used in a compatibility mode [20].

We think that the experience we have got in developing MIBIBTEX may be useful for other analogous projects. In a first section, we briefly recall the chronology of this development. As it could be seen, this development has not been linear, and the two next following sections focus on the problems we had to face. We explain how we have determined which criteria are accurate when a programming language is to be chosen for such an application. Then we show how the compatibility with 'old' data and the integration of modern features should be managed.

1 MIBIBTEX's Chronology

Oct. 2000 MIBIBTEX's design begins: the syntax of .bib files is enriched with multilingual annotations. Version 1.1's prototype is written using the C programming language and tries to reuse parts of 'old' BIBTEX's program as far as possible.

May 2001 The first article about MIBIBTEX is [9]. Later, the experience of developing MIBIBTEX's Version 1.1 is described in [10].

May 2002 By discussing with some people at the EuroBachoTEX conference, we realise that the conventions for bibliography styles are too diverse, even if we consider only those of European countries. We realise that this first approach is quite unsuitable, unless defining a new version of the `bst` language. So we decide to explore two directions. First, we develop a questionnaire about problems and conventions concerning bibliography styles used within European countries. Second, we begin a prototype in Scheme implementing the `bst` language [11]. Initially, this prototype is devoted to experiments about improving this language in a second version (1.2).

Jan. 2003 Version 1.2 is stalled. The new version (1.3) is built out of XML formats. The `nbst` language is designed and presented at [12, 13]. We explain in [14] how the results of our questionnaire have influenced this new direction.

Feb. 2004 It appears to us that MIBIBTEX should be developed using a very high-level program-

ming language, higher than C. So we consider again the prototype in Scheme, we sketched in 2002. SXML⁷ [25] is chosen as the representation of XML texts in Scheme. Some parts of MIBIBTEX are directly reprogrammed from C to Scheme. About the other parts, this prototype is a good basis for much experiment [16].

Nov. 2004 The version written in C is definitely dropped out, whereas the version in Scheme is adapted in order to get much efficiency and becomes the 'official' MIBIBTEX [18].

Sep. 2005 We decided to freeze MIBIBTEX's design and concentrate only on finishing programming. Many Scheme functions are rewritten in conformity to SRFIs⁸ [39].

May 2006 A working version is almost finished, except for the interface with the `kpathsea` library.

May 2007 Public availability of MIBIBTEX's Version 1.3.

Besides, let us make precise that MIBIBTEX is not our only task. As an Assistant Professor in our university, we teach Computer Science. We also participate in other projects. As a consequence, MIBIBTEX's development has been somewhat anarchic: we hardly worked on it for two or three months, put it aside for one or two months, and so on. Last, we have supervised some student projects about graphical tools around MIBIBTEX [2, 8], programmed using Ruby [31], but concerning the development of the MIBIBTEX program itself, we have done it alone.

2 Choice of an implementation language

There are several programming paradigms: imperative, functional, and logic programming. There are also several ways to implement a programming language: interpretation and compilation. Some paradigms are more accurate, according to the domain of interest. Likewise, some interpreted languages are more accurate if you want to program a prototype quickly and are just interested in performing some experiment.⁹ But compiled languages are often preferable if programs' efficiency is crucial. Besides, the level of a programming language has some influence on development: in a high-level language, low-level details of structures' implementation do not have to be made explicit, so development is

⁷ Scheme implementation of XML.

⁸ Scheme Requests for Implementation. That is an effort to coordinate libraries and other additions to the Scheme language between implementations.

⁹ That is the case for the graphical tools around MIBIBTEX programmed in Ruby by our students [2, 8].

⁵ New Bibliography STyles.

⁶ eXtensible Language Stylesheet Transformations, the language of transformations used for XML documents [43].

quicker, and programs that result in are more concise, nearer to a mathematical model.

In addition to these general considerations, let us recall that we aim to replace an existing program by a new one. This new program is supposed to do better than the ‘old’ one. ‘To do better’ may mean ‘to have more functionalities, more expressive power’, but for sake of credibility, it is preferable for the new program to be as efficient as the ‘old’ one. Let us not forget that **T_EX** and **BIB_TEX** are written using an old style of programming—more precisely, a monolithic style used in the 1970’s–1980’s—based on global variables mainly, without abstract data types. Choosing a language implemented efficiently is crucial: as a counter-example, *N_TS*, written using **J**ava, has been reported 100 times slower than **T_EX** [42, § 5].

That is why we wrote MIBIBTEX’s first version using C, because of its efficiency. In addition, this language is portable on most operating systems. And to make our program modular, we defined precise rules for naming procedures [10, § 3]. But two problems appeared.

First, MIBIBTEX’s development has not been a daily task, as abovementioned. Even if we are personally able to program large applications in C, it was difficult to put aside a C program and resume it later: from this point of view, C is not a very high-level language. Besides, let us not forget that we are working within an open domain, as natural languages are. Some change may be needed because of new features concerning languages that had not yet been integrated into MIBIBTEX’s framework. The higher the level, the more easy such change will be applied.

Second, we want end-users of MIBIBTEX to be able to influence the behaviour of this program. For example, many **BIB_TEX** users put **L_AT_EX** commands inside values associated with fields of .bib files, in order to increase expressive power within bibliographical data. These users should be able to specify how to handle such commands when .bib files are converted into XML trees. In particular, that is useful if MIBIBTEX is used to produce outputs for other word processors than **L_AT_EX** [21]. How to do that in C? unless defining a mini-language to express such functions? In this case, using a script language is a better choice . . . provided that this language is efficient. Another choice is a **Lisp**¹⁰ dialect, as did in **emacs** [40]: end-users can customise **emacs**’ behaviour by expressions using the Emacs Lisp language [30]. This choice is homogeneous: the whole of the **emacs** pro-

gram is expressed using **Emacs Lisp**, except for the implementation of low-level functionalities.

Finally, our choice was Scheme, the modern dialect of **Lisp**. We confess that we are personally attracted by functional programming languages, because they can abstract procedures as well as data: in this sense, they are very high-level programming languages. Concerning Scheme, it seems to us to be undebatable that it has very good expressive power. In addition, it allows some operations to be programmed ‘impurely’, by side effects, like in imperative programming, in order to increase efficiency. However, we use this feature parsimoniously, on local variables, because it breaks principles of functional programming. We have defined precise rules for naming variables, as we did in C for the first version, in order to emphasise the modular decomposition of our program [19]. Last but not least, Scheme programs may be interpreted—when software is being developed—or compiled, in which case they are more efficient. As a good example of Scheme implementation, **bigloo** [38] compiles Scheme functions by transforming them into C functions, then these C functions are compiled, in turn.

If we compare the two developments in C and Scheme, the latter is better, as it is expected from a very high-level programming language. But programming an application related to **T_EX** using a language other than C reveals a drawback: the **kpathsea** library [3] is written in C. Let us recall that **kpathsea** implements functions navigating through the TDS.¹¹ In particular, such functions localise the files containing the specification of a class for a **L_AT_EX** document or a bibliography style when **BIB_TEX** runs. If there is a compatibility mode, for ‘old’ bibliography styles written in **bst**, the functions of this compatibility mode should be able to localise such files, too. Likewise, ‘new’ bibliography styles written in **nbst**, should be localised by means of an analogous method. This implies that the language—or, at least, an implementation of the language—used for our software includes an interface with C.

Of course, what we expose above proceeds from general considerations. After all, we do not know if **BIB_TEX++** [4]—a successor of **BIB_TEX** based on **J**ava, bibliography styles are written in **J**ava—is very less efficient than **BIB_TEX**. This may not be the case. The advantages of script languages in such development appear if we consider **Bibulus** [45], another successor of **BIB_TEX**, written using Perl.¹² It has developed quicker than MIBIBTEX, but is

¹¹ **T_EX Directory Structure**.

¹² **Practical Extraction Report Language**. A didactic introduction to this language is [44].

¹⁰ **LIS_T** Processor.

'less' multilingual and uses BIBTEX when it runs. That is, Bibulus does not replace BIBTEX wholly, as MIBIBTEX attempts to do. In addition, there is an example where the need of a programming language with higher level than C appeared: the project of moving Ω —a successor of T_EX—into a C++ platform [36].

We personally think that an implementation of $\mathcal{N}\mathcal{T}\mathcal{S}$ in Common Lisp [41]—what was planned initially—would have been preferable. As mentioned in [46], the object-oriented features of Common Lisp (CLOS¹³) have been added to the language's basis—like C++ object-oriented functionnalities have been added to C—but the language itself is not actually object-oriented. In [46], this point is viewed as a drawback. First, we personally think that everything is not an object, from a point of view related to conception. Second, Common Lisp, even if it is a functional programming language, allows some operations to be performed more efficiently by means of side effects, like Scheme.¹⁴ But Common Lisp's standard does not specify an interface with C, like Scheme's, although some implementations provide this service. However, we personally prefer Scheme, simpler and more modern.

3 Choice of strategy

3.1 Languages

T_EX & Co. have been wonderful programs since the date they came out. However, they behave very nicely, but syntaxes are quite archaic. T_EX's is not homogeneous—although L_AT_EX 2_E and L_AT_EX 3 [32] try to correct this point—for example, different delimitations are used to change size ('{\small ...}') or face ('\textbf{...}'). BIBTEX's syntax suffers from lack of expressive power: for example, the only way to put a brace within a field's value is to give its code number by '\symbol{...}'. 'Semantically', T_EX's language provides many intelligent features, as mentionned in [6], but does not meet a modern style of programming. Likewise, .bib files' syntax can express only 'verbatim' values, except for some 'tricks' like inserting some '-' characters for a range of page numbers. The specification of stuctured values like person or organisation names is easy for simple cases, but quickly becomes obscure in more complicated cases [22].

In addition, new syntactic sugar may be needed to meet some new requirements. As an example, [23] points out that the arguments of some macros—e.g., \catcode—are not easily parseable. As an

¹³ Common Lisp Object System.

¹⁴ Emacs Lisp, too, and the programs of emacs largely use this feature.

other example, the ConTEXt format [7] put good settlement into action for an homogeneous expression of setup commands, by means of 'key=value' syntax:

```
\setuplayout [backspace=4cm,topspace=2.5cm]
```

Nevertheless, is it reasonable to add more and more syntactic sugar to such old-fashioned syntax? Would the definition of new languages not be preferable? Of course, the present languages of T_EX and BIBTEX will still remain to be used, due to the huge number of files using them and developed by end-users. But if a new language is designed, it should become the usual way to deal with the new program. Of course, end-users will have to get used with the new language. But that can be done progressively and some synergy between developers and users may cause this new language to be improved if need be.

In addition, let us remark that in our case, the new language for bibliography styles (nbst) is close to XSLT, so we think that users familiar with the former can get used to the latter easily.

3.2 New services

Now it is admitted that composite tasks are not to be done by a monolithic program, but by means of a cooperation among several programs. From this point of view, the cooperation between L_AT_EX and BIBTEX is exemplar. But BIBTEX is too strongly related to L_AT_EX. BIBTEX can be used to build bibliography for ConTEXt documents, but because this word processor belongs to T_EX family. On the contrary, writing a converter from BIBTEX to HTML¹⁵ by means of the bst language is impossible without loss of quality: for example, the unbreakable space character is represented by '-'—as in T_EX—when names are formatted [22], and this convention cannot be changed.¹⁶ We see that such problems can be avoided by considering an XML-like language as a central format. In our case, generating bibliographies according to other formats than L_AT_EX's should be easy since the L_AT_EX commands end-users put into .bib files are removed when these files are parsed. This point is detailed in [17, 21].

4 Conclusion

Last but not least, we have enjoyed to design and implement MIBIBTEX, even if this development back-tracked several times. In addition, we think that this development shows the difficulties related to such a

¹⁵ HyperText Markup Language. Readers interested in an introduction to this language can refer to [33].

¹⁶ In fact, there are such converters, an example being BIBTEX2HTML [5], written using Objective Caml [29], a functional programming language.

task. Two parts have to be managed in parallel. The first part is *reverse engineering*, that is, guessing the conception from the program. The second: enlarging what already exists. In comparison with ‘classical’ development of a new program from scratch, tests concerning the compatibility mode are easy to perform: just comparing what is given by the two programs, the ‘old’ one becoming an oracle. But reaching homogeneous conception is not obvious if we want to keep backward compatibility. Nevertheless, we hope that we have done some satisfactory work.

5 Acknowledgements

Many thanks to Jerzy B. Ludwichowski, who has written the Polish translation of the abstract.

References

- [1] William ADAMS, ed.: *TUG 2003 Proceedings*, Vol. 24:3. TUGboat. July 2003.
- [2] Cédric BASSETTI and Christian BON: *Interactive Specification of bibliography styles for MIBIBTEX*. Report of student project. University of Franche-Comté. May 2006.
- [3] Karl BERRY and Olaf WEBER: *Kpathsea library for Version 3.3.7*. November 2001. Part of LATEX’s distribution.
- [4] Emmanuel DONIN DE ROSIERE: *From Stack Removing in Stack-Based Languages to BIBTEX++*. Master’s thesis, ENSTBr, Brest. 2003.
- [5] Jean-Christophe FILLIATRE and Claude MARCHÉ: *The BIBTEX2HTML Home Page*. June 2006. <http://www.lri.fr/~filliatr/bibtex2html/>.
- [6] Jonathan FINE: “*TeX as a Callable Function*”. In: *EuroTEX 2002*, pp. 26–30. Bachotek, Poland. April 2002.
- [7] Hans HAGEN: *ConTEXt, the Manual*. November 2001. <http://www.pragma-ade.com/general/manuals/cont-enc.pdf>.
- [8] Stéphane HENRY and Jérôme VOINOT: *Interface for MIBIBTEX. Getting Bibliographical Entries Interactively*. Report of student project. University of Franche-Comté. May 2005.
- [9] Jean-Michel HUFFLEN : « Vers une extension multilingue de BIBTEX ». *Cahiers GUTenberg*, Vol. 39–40, p. 23–38. In *Actes du Congrès GUTenberg 2001*, Metz. Mai 2001.
- [10] Jean-Michel HUFFLEN: “Lessons from a Bibliography Program’s Reimplementation”. In: Mark VAN DEN BRAND and Ralf LÄMMEL, eds., *LDTA 2002*, Vol. 65.3 of *ENTCS*. Elsevier, Grenoble, France. April 2002.
- [11] Jean-Michel HUFFLEN: *Interaktive BIBTEX-Programmierung*. DANTE, Herbstagung 2002, Augsburg. Oktober 2002.
- [12] Jean-Michel HUFFLEN: *Die neue Sprache für MIBIBTEX*. DANTE 2003, Bremen. April 2003.
- [13] Jean-Michel HUFFLEN: “Mixing Two Bibliography Style Languages”. In: Barrett R. BRYANT and João SARAIVA, eds., *LDTA 2003*, Vol. 82.3 of *ENTCS*. Elsevier, Warsaw, Poland. April 2003.
- [14] Jean-Michel HUFFLEN: “European Bibliography Styles and MIBIBTEX”. *TUGboat*, Vol. 24, no. 3, pp. 489–498. EuroTEX 2003, Brest, France. June 2003.
- [15] Jean-Michel HUFFLEN: “MIBIBTEX’s Version 1.3”. *TUGboat*, Vol. 24, no. 2, pp. 249–262. July 2003.
- [16] Jean-Michel HUFFLEN: “A Tour around MIBIBTEX and Its Implementation(s)”. *Biuletyn GUST*, Vol. 20, pp. 21–28. In *BachotEX 2004 conference*. April 2004.
- [17] Jean-Michel HUFFLEN: “MIBIBTEX: beyond LATEX”. In: Apostolos SYROPOULOS, Karl BERRY, Yannis HARALAMBOUS, Baden HUGUES, Steven PETER and John PLAICE, eds., *International Conference on TEX, XML, and Digital Typography*, Vol. 3130 of *LNCS*, pp. 203–215. Springer, Xanthi, Greece. August 2004.
- [18] Jean-Michel HUFFLEN: *Beschreibung der MIBIBTEX-Implementierung mit Scheme*. DANTE 2004, Herbstagung, Hannover. Oktober 2004.
- [19] Jean-Michel HUFFLEN: “Implementing a Bibliography Processor in Scheme”. In: J. Michael ASHLEY and Michel SPERBER, eds., *Proc. of the 6th Workshop on Scheme and Functional Programming*, Vol. 619 of *Indiana University Computer Science Department*, pp. 77–87. Tallinn. September 2005.
- [20] Jean-Michel HUFFLEN: “BIBTEX, MIBIBTEX and Bibliography Styles”. *Biuletyn GUST*, Vol. 23, pp. 76–80. In *BachotEX 2006 conference*. April 2006.
- [21] Jean-Michel HUFFLEN: “MIBIBTEX Meets ConTEXt”. *TUGboat*, Vol. 27, no. 1, pp. 76–82. EuroTEX 2006 proceedings, Debrecen, Hungary. July 2006.
- [22] Jean-Michel HUFFLEN: “Names in BIBTEX and MIBIBTEX”. *TUGboat*, Vol. 27, no. 2, pp. 243–253. TUG 2006 proceedings, Marrakesh, Morocco. November 2006.

- [23] David KASTRUP: “Designing an Implementation Language for a \TeX Successor”. In: *Proc. Euro\TeX 2005*, pp. 71–75. February 2005.
- [24] Richard KELSEY, William D. CLINGER, Jonathan A. REES, Harold ABELSON, Norman I. ADAMS IV, David H. BARTLEY, Gary BROOKS, R. Kent DYBVIG, Daniel P. FRIEDMAN, Robert HALSTEAD, Chris HANSON, Christopher T. HAYNES, Eugene Edmund KOHLBECKER, JR, Donald OXLEY, Kent M. PITMAN, Guillermo J. ROZAS, Guy Lewis STEELE, JR, Gerald Jay SUSSMAN and Mitchell WAND: “Revised⁵ Report on the Algorithmic Language Scheme”. *HOSC*, Vol. 11, no. 1, pp. 7–105. August 1998.
- [25] Oleg E. KISELYOV: *XML and Scheme*. September 2005. <http://okmij.org/ftp/Scheme/xml.html>.
- [26] Donald Ervin KNUTH: “The Future of \TeX and METAFONT”. *TUGboat*, Vol. 11, no. 4, pp. 489. December 1990.
- [27] Joachim LAMMARSCH: “The History of $\mathcal{N}\mathcal{T}\mathcal{S}$ ”. In: *Euro\TeX 1999*, pp. 228–232. Heidelberg (Germany). September 1999.
- [28] Leslie LAMPORT: *L^AT_EX: A Document Preparation System. User’s Guide and Reference Manual*. Addison-Wesley Publishing Company, Reading, Massachusetts. 1994.
- [29] Xavier LEROY, Damien DOLIGEZ, Jacques GARRIGUE, Didier RÉMY and Jérôme VOUILLOU: *The Objective Caml System. Release 0.9. Documentation and User’s Manual*. 2004. <http://caml.inria.fr/pub/docs/manual-ocaml/index.html>.
- [30] Bill LEWIS, Dan LALIBERTE, Richard M. STALLMAND and THE GNU MANUAL GROUP: *GNU Emacs Lisp Reference Manual for Emacs Version 21. Revision 2.8*. January 2002. <http://www.gnu.org/software/emacs/elisp-manual/>.
- [31] Yukihiro MATSUMOTO: *Ruby in a Nutshell*. O’Reilly. English translation by David L. Reynolds, Jr. November 2001.
- [32] Frank MITTELBACH and Rainer SCHÖPF: “Towards L^AT_EX 3.0”. *TUGboat*, Vol. 12, no. 1, pp. 74–79. March 1991.
- [33] Chuck MUSCIANO and Bill KENNEDY: *HTML & XHTML: The Definitive Guide*. 5th edition. O’Reilly & Associates, Inc. August 2002.
- [34] Oren PATASHNIK: *Designing BIB\TeX Styles*. February 1988. Part of the BIB\TeX distribution.
- [35] Oren PATASHNIK: *BIB\TeXing*. February 1988. Part of the BIB\TeX distribution.
- [36] John PLAICE and Paul SWOBODA: “Moving Omega to a C++-Based Platform”. *Buletyn Polskiej Grupy Użytkowników Systemu \TeX*, Vol. 20, pp. 3–5. In *Bacho\TeX 2004 conference*. April 2004.
- [37] Erik T. RAY: *Learning XML*. O’Reilly & Associates, Inc. January 2001.
- [38] Manuel SERRANO: *Bigloo. A Practical Scheme Compiler. User Manual for Version 2.9a*. December 2006.
- [39] *Scheme Requests for Implementation*. February 2007. <http://srfi.schemers.org>.
- [40] Richard M. STALLMAN: *GNU emacs Manual*. January 2007. <http://www.gnu.org/software/emacs/manual/>.
- [41] Guy Lewis STEELE, JR., with Scott E. FAHLMAN, Richard P. GABRIEL, David A. MOON, Daniel L. WEINREB, Daniel Gureasko BOBROW, Linda G. DEMICHEL, Sonya E. KEENE, Gregor KICZALES, Crispin PERDUE, Kent M. PITMAN, Richard WATERS and Jon L WHITE: *COMMON LISP. The Language. Second Edition*. Digital Press. 1990.
- [42] Philip TAYLOR, Jiří ZLATUŠKA and Karel SKOUPÝ: “The $\mathcal{N}\mathcal{T}\mathcal{S}$ Project: from Conception to Implementation”. *Cahiers GUTenberg*, Vol. 35–36, pp. 53–77. May 2000.
- [43] W3C: *XSL Transformations (XSLT)*. Version 1.0. W3C Recommendation. Edited by James Clark. November 1999. <http://www.w3.org/TR/1999/REC-xslt-19991116>.
- [44] Larry WALL, Tom CHRISTIANSEN and Jon ORWANT: *Programming Perl*. 3rd edition. O’Reilly & Associates, Inc. July 2000.
- [45] Thomas WIDMAN: “Bibulus—a Perl XML Replacement for BIB\TeX”. In: *Euro\TeX 2003*, pp. 137–141. ENSTB. June 2003.
- [46] Jiří ZLATUŠKA: “ $\mathcal{N}\mathcal{T}\mathcal{S}$: Programming Languages and Paradigms”. In: *Euro\TeX 1999*, pp. 241–245. Heidelberg (Germany). September 1999.