Directional Discrete Cosine Transform for Handwritten Script Identification

Mallikarjun Hangarge[†], K.C. Santosh[‡], Rajmohan Pardeshi[†]

[†]Department of Computer Science

Karnatak Arts, Science & Commerce College, Bidar, INDIA

[‡]LORIA - Université de Lorraine

BP - 239, Loria Campus Scientifique, FRANCE

Email: mhangarge@yahoo.co.in, Santosh.KC@loria.fr, rajkascc@ieee.org

Abstract—This paper presents directional discrete cosine transforms (D-DCT) based word level handwritten script identification. The conventional discrete cosine transform (DCT) emphasizes vertical and horizontal energies of an image and de-emphasizes directional edge information, which of course plays a significant role in shape analysis problem, in particular. Conventional DCT however, is not efficient in characterizing the images where directional edges are dominant. In this paper, we investigate two different methods to capture directional edge information, one by performing 1D-DCT along left and right diagonals of an image, and another by decomposing 2D-DCT coefficients in left and right diagonals. The mean and standard deviations of left and right diagonals of DCT coefficients are computed and are used for the classification of words using linear discriminant analysis (LDA) and K -nearest neighbour (K -NN). We validate the method over 9000 words belonging to six different scripts. The classification of words is performed at bi-scripts, tri-scripts and multi-scripts scenarios and accomplished the identification accuracies respectively as 96.95%, 96.42% and 85.77% in average.

I. INTRODUCTION

Optical character recognition (OCR) is one of the challenging areas of research in pattern recognition, which is basically script dependent. Therefore, to facilitate the OCR process, script separation is necessary. Unlike the other scripts, in context of Indian documents, for instance, we come across with multi-script documents such as bank cheques, application forms and railway reservation forms. An example of bi-script document is shown in Fig. 1. In this paper, we are primarily focused on handwritten script identification. It is basically defined as an automatic identification of different script zones in a text document. It can be done at paragraph, line or word level. Word level script identification is relatively significant than paragraph or line level. This task is simpler when we deal with printed documents, whereas it is harder in case of handwritten documents because of the unconstrained character sizes, gaps between words, lines, writing style, etc. With these factors, we have motivated to outline a generic framework to deal with both printed and handwritten script identification at bottom level i.e., word level.

Over the last three decades, besides the work on printed text, few works are reported on handwritten text script identification of Indic scripts. Almost all the methods either employed global or local and combinations of both global and local features. Primarily, global features used in [1]–[6] are based

on DCT, DWT, Gabor, steerable pyramids, and the Radon transform. The local features, for example, shape features of connected components are employed in [7]–[12]. The combination of these are employed in [13] and called it as global method. A detailed review of literature of script identification is presented in [14], and especially, a brief review on Indic handwritten script identification in [15]. In a similar way, very recently, one can find the use of both features to separate handwritten and printed text [16]. Based on the analysis of the above techniques, we understand that, aforementioned methods have their own merits and demerits. Explicitly, local features are script dependent, sensitive to noise, skew, segmentation and are slower in computation. But, they are efficient in extracting dominant features, particularly, directional strokes of small size images [9], for instance, connected components. Global features are efficient in characterizing large size texture patterns, for example, text blocks. They are robust to noise, small skew, and are faster in computation. However, they are weak in extracting directional energies of small size images, connected components, for instance. In particular, the DCT and wavelet features employed in [1] for classifying text blocks are not potential to sustain their performance in case of word image. The global method also suffers with the issues like time complexity, segmentation, and image size. These quick observations indicate that global method is the better choice than the local [14]. Therefore, in this paper, we have presented a global technique based on directional DCT which is efficient to recover the above limitations.

The paper is organized as follows. We start by detailing the proposed approach in Section II. It mainly includes feature extraction techniques and classifier. Full Experimental results are reported in Section III, where result analysis in accordance with the scripts employed is provided. In Section IV, the paper is concluded.

II. PROPOSED METHOD

The primary aim is to perform word-level script identification. Words are first extracted from each document based on the morphological operators where we are primarily employed connected component analysis. The extracted words then represented with DCT features and its variant. For classification, two different well-known classifiers: LDA and K -NN are employed. The preliminary work is provided in [17].

1D-DCT and then standard deviation σ_1 using

$$C(u) = \alpha(u) \sum_{\mu=0}^{N-1} f(\delta) \cos \left[\frac{\pi(2\delta+1)u}{2N} \right], \quad (4)$$

for $u = 0, 1, 2, \dots, N-1$ and N is the number of pixels in μ ,

$$\sigma_1 = \sqrt{\frac{1}{n-1} \sum_{u=1}^n (C(u) - \bar{C}(u))^2}, \quad (5)$$

where $u = 1, 2, \dots, n$ and n is the number of DCT coefficients in $C(u)$. The standard deviation σ_1 is a scalar value. Secondly, β number of upper right diagonals of A are extracted and computed their 1D-DCTs as mentioned in Eq. 4. The standard deviations of β diagonals are obtained using

$$\sigma_\beta = \sqrt{\frac{1}{n-1} \sum_{u=1}^n (C(u)_\beta - \bar{C}(u)_\beta)^2}, \quad (6)$$

where $u = 1, \dots, n$ and $\beta = 1, \dots, N-2$. σ_β is a column vector of size $N-2 \times 1$. Then, by appending the value of σ_1 and a zero into σ_β , we get first feature $f1$ of dimension $N \times 1$. Similarly, α number of lower left diagonals of A are extracted and computed their 1D-DCTs as mentioned in Eq. 1. The standard deviations of α diagonals are obtained using

$$\sigma_\alpha = \sqrt{\frac{1}{n-1} \sum_{u=1}^n (C(u)_\alpha - \bar{C}(u)_\alpha)^2}, \quad (7)$$

where $m = 1, \dots, N-2$ and σ_α is a column vector of size $N-2 \times 1$. By appending two zeros into σ_α , we get second feature $f2$ of dimension $N \times 1$. In this way, features $f3$ and $f4$ are computed by flipping the input matrix A . The flipped matrix is denoted by A^f and upper, lower and principal diagonals are by β^f , α^f and δ^f respectively. Finally, standard deviations of 1D-DCT coefficients of horizontal and vertical frequency responses of A are computed to obtain features $f5$ and $f6$ respectively. Thus, an integrated feature vector $F = \{f1_{N \times 1}, \dots, f6_{N \times 1}\}$ of size $N \times 6$ is formed. To reduce the dimension of the feature vector, again computed mean and standard deviations of $f1_{N \times 1}, \dots, f6_{N \times 1}$ and reduced dimension $N \times 6$ to 12×1 (six means and six standard deviations) as the central tendency measure values of each word image and the same is used for classification.

Directional Discrete Cosine Transforms (D-DCT). In this method, first, we have computed 2D-DCT of a word image. Let the 2D-DCT coefficient matrix of a word image be D . Then, principal diagonal, upper $N-2$ and lower $N-2$ diagonals of D is extracted before and after flipping D , and further computed their standard deviations respectively as discussed in the aforementioned paragraph. Meanwhile, we have also extracted features based on conventional DCT. In this case, its coefficient matrix is divided into four zones and standard deviation of each zone is computed. Thus, a feature vector of four features is formed.

C. Classification

Linear Discriminant Analysis is one of the most commonly used classification technique. It preserves class discriminating information to the higher extent by reducing dimensionality of feature space. It also maximizes separability between the

classes by maximizing the ratio of between-class variance to the withinclass variance. In this paper, LDA is employed on a dataset $X = [x_1, \dots, x_i]$ of dimension $N \times 12$ ($N=9000$) and the samples x_i are belongs to one of the class C_i , where $i = 1, \dots, 6$. Further, the dimension of x_i is $m \times p$, where $m = 1, \dots, 1500$ and $p = 1, \dots, 12$. Then the classification function is defined as

$$g(X) = W^T X, \quad (8)$$

where W is the linear projection, and which maximizes between-class scatter

$$S_b = S_1 + S_2 + \dots + S_6 = \sum_{i=1}^6 \sum_{x \in C_i} (X - \mu_i)(X - \mu_i)^T, \quad (9)$$

whereas it minimizes the within-class scatter

$$S_w = \sum_i m_i (\mu_i - \mu)(\mu_i - \mu)^T, \quad (10)$$

where μ_i is the mean over class C_i , μ is the mean over all samples, and m_i is the number of samples in class C_i . The classification of a new sample x of class label $\omega \in C_i$ is done based on the nearest neighbor classification rule. For this purpose, the Euclidean distance d of $g(X)$ and the centers $V_i = W^T \mu_i$ in LDA space are compared

$$\omega = \operatorname{argmin}_{1 \leq i \leq c} d(g(X), V_i) \quad (11)$$

To comprehend the performance of LDA, another traditional classifier i.e., K -NN is used. Basically K -NN stores the training data X . Then finds the minimum D distance between training sample X and testing pattern Y using

$$D(X, Y) = \sqrt{(X - Y_i)^T (X - Y_i)}. \quad (12)$$

III. EXPERIMENTS

A. Datasets.

There is no publicly available dataset of Indic script at present. Therefore, a dataset of 9000 handwritten text words of six scripts, namely Roman ($\mathcal{R}$), Devanagari ($\mathcal{D}$), Kannada ($\mathcal{K}$), Telugu ($\mathcal{T}_e$), Tamil ($\mathcal{T}_a$) and Malayalam ($\mathcal{M}$) (1500 words of each script) is created. For generating a dataset, we have selected a paragraph of printed text from the various documents related to History, Arts, Medical, Religious and Science. This enables us to have more number of unlike words in dataset. The selected paragraphs of text are distributed among 20 writers belong to various professions and age groups. Each script is written by a different set of 20 writers. Each writer has written 75 words. The writers are asked to write the text provided for them on a A4 size paper. These papers are digitized by a scanner with a resolution of 300 dpi.

B. Evaluation protocol

To evaluate the performance of the method, $\mathbb{K}$ -fold cross validation (CV) has been implemented unlike traditional dichotomous classification. In $\mathbb{K}$ -fold CV, the original sample for every dataset is randomly partitioned into $\mathbb{K}$ sub-samples. Of the $\mathbb{K}$ sub-samples, a single sub-sample is used for validation, and the remaining $\mathbb{K} - 1$ sub-samples are used for training. This process is then repeated for $\mathbb{K}$ -folds, with each of the $\mathbb{K}$ sub-samples used exactly once. Eventually, a single value results from averaging all. In our tests, we use $\mathbb{K} = 10$.

TABLE I. BI-SCRIPT IDENTIFICATION RESULTS IN % WITH LDA (LOWER TRIANGLE RESULTS ARE FROM DDI AND UPPER TRIANGLE ARE FROM D-DCT).

Script	$\mathcal{R}$	$\mathcal{D}$	$\mathcal{K}$	$\mathcal{T}_{\mathcal{E}}$	$\mathcal{T}_{\mathcal{A}}$	$\mathcal{M}$	Average
$\mathcal{R}$	-	99.00	96.23	96.60	98.90	97.86	97.72
$\mathcal{D}$	88.03	-	97.90	99.16	98.33	98.46	98.46
$\mathcal{K}$	92.80	94.83	-	85.73	95.03	95.66	92.14
$\mathcal{T}_{\mathcal{E}}$	95.50	94.93	87.50	-	96.03	98.66	97.35
$\mathcal{T}_{\mathcal{A}}$	97.53	96.80	92.63	93.00	-	99.06	99.10
$\mathcal{M}$	98.00	97.37	92.73	95.30	91.17	-	96.95
Average	94.37	95.98	90.96	95.15	91.17	93.33	-

TABLE II. BI-SCRIPT IDENTIFICATION (IN %) WITH K -NN (LOWER TRIANGLE RESULTS ARE FROM DDI AND UPPER TRIANGLE ARE FROM D-DCT).

Script	$\mathcal{R}$	$\mathcal{D}$	$\mathcal{K}$	$\mathcal{T}_{\mathcal{E}}$	$\mathcal{T}_{\mathcal{A}}$	$\mathcal{M}$	Average
$\mathcal{R}$	-	95.57	92.23	92.47	97.03	97.20	94.90
$\mathcal{D}$	91.76	-	97.77	96.40	97.90	98.17	97.56
$\mathcal{K}$	94.8	98.20	-	84.70	93.93	93.67	90.77
$\mathcal{T}_{\mathcal{E}}$	96.6	95.80	94.13	-	95.73	95.30	95.52
$\mathcal{T}_{\mathcal{A}}$	97.26	97.67	94.40	96.17	-	97.67	97.67
$\mathcal{M}$	98.2	98.47	95.86	95.06	92.86	-	95.28
Average	95.73	97.53	94.80	95.62	92.87	95.31	-

TABLE III. TRI-SCRIPT IDENTIFICATION (IN %) WITH LDA.

Script	$\mathcal{R}\mathcal{D}\mathcal{K}$	$\mathcal{R}\mathcal{D}\mathcal{T}_{\mathcal{E}}$	$\mathcal{R}\mathcal{D}\mathcal{T}_{\mathcal{A}}$	$\mathcal{R}\mathcal{D}\mathcal{M}$	Average
DDI	85.38	86.37	89.42	89.44	87.65
D-DCT	95.56	95.76	97.76	96.60	96.42

TABLE IV. TRI-SCRIPT IDENTIFICATION (IN %) WITH K -NN.

Script	$\mathcal{R}\mathcal{D}\mathcal{K}$	$\mathcal{R}\mathcal{D}\mathcal{T}_{\mathcal{E}}$	$\mathcal{R}\mathcal{D}\mathcal{T}_{\mathcal{A}}$	$\mathcal{R}\mathcal{D}\mathcal{M}$	Average
DDI	90.51	91.38	92.27	93.11	91.82
D-DCT	92.18	92.00	94.89	95.29	93.59

C. Results and Analysis

The bi-script identification results are presented at lower left triangle of Table I and II, computed based on DDI method using LDA and K -NN classifiers respectively. The performance of K -NN is notable in classifying five bi-scripts with an average accuracy of 95.31%, whereas LDA is 93.33%. It also shows promising performance in classifying bi-script combinations such as Roman-Devanagari, Roman-Kannada, Roman-Telugu, Roman-Tamil, and Roman-Malayalam with an average identification accuracy as 95.73% as compared to 94.37% of LDA (see first column of Table I and II). In case of bi-script combinations, namely Devanagari-Kannada, Devanagari-Telugu, Devanagari-Tamil, Devanagari-Malayalam, an average identification accuracy is 97.53% with K -NN and 95.98% with LDA. Tri-script and multi-script identification results of both the methods are presented in Table III, V, IV and VI. The success of K -NN continues with tri-script classification and showed average identification accuracy as 91.8% against 87.65% of LDA. Multi-script identification results are 86.50% and 76.00% with K -NN and LDA respectively. In addition, the worst performance of the LDA classifier is noticed in classifying Kannada and Telugu scripts, that is nearly 85.0% but K -NN showed outstanding performance of 94.13%. Taken as a whole, a method of DDI with K -NN showed outstanding performance as compared to LDA with DDI scheme.

The results presented at upper right triangles of Table I and II are from D-DCT method, computed using LDA and K -NN classifiers. An average bi-script identification accuracy achieved using LDA and K -NN classifiers is 96.95% and 95.28% respectively. Overall, the performance of LDA is

TABLE V. MULTI-SCRIPT IDENTIFICATION (IN %) WITH LDA.

Script	$\mathcal{R}$	$\mathcal{D}$	$\mathcal{K}$	$\mathcal{T}_{\mathcal{E}}$	$\mathcal{T}_{\mathcal{A}}$	$\mathcal{M}$	Average
DDI	80.00	80.33	66.73	76.33	73.60	79.00	76.00
D-DCT	89.70	95.60	67.133	79.87	90.93	91.40	85.77

TABLE VI. MULTI-SCRIPT IDENTIFICATION (IN %) WITH K -NN.

Script	$\mathcal{R}$	$\mathcal{D}$	$\mathcal{K}$	$\mathcal{T}_{\mathcal{E}}$	$\mathcal{T}_{\mathcal{A}}$	$\mathcal{M}$	Average
DDI	83.70	88.60	86.40	87.30	85.80	87.30	86.50
D-DCT	83.50	92.40	77.60	80.30	91.20	89.10	85.70

remarkable in classifying five bi-scripts and four tri-scripts combinations as compared to K -NN. For example, tri-script average identification accuracy is 96.42% with LDA, whereas 93.58% with K -NN. Furthermore, the highest bi-script recognition accuracy of LDA is 99.16% for Devanagari-Telugu combination, whereas, 96.40% in case of K -NN. In case of multi-script identification, the performance of the both the classifiers closely remains same. These observations generally show LDA is discriminant over different scripts based on D-DCT features wherein K -NN is not. These paragraphs signify the performance of the classifiers that depends on the nature of features under study.

This paragraph emphasizes the weaknesses of the proposed algorithm. The DDI features with LDA has poor performance in discriminating between Kannada and Telugu scripts. The primary reason is shape similarity between characters between the scripts. Both the classifiers with D-DCT features do not provide efficiency in classifying (Table I and II): Roman-Kannada and Roman-Telugu bi-script combinations in comparison to other combinations. It is due to the writing style of the writer. The native Kannada writer has written Roman script. Therefore, writing style of Kannada is imitated while writing Roman scripts. This is an interesting observation, which is experimentally validated, by performing an experimentation with IAM dataset of Roman script (which are not written by Indian writers). As an example, we have computed horizontal features of 20 text words of IAM database and Kannada script. Meanwhile, horizontal features of 20 text words of Indian Roman (i.e., Roman script written by Indians) and Kannada script. These are illustrated through plots (cf. Fig. 3) and showed less separability between the features of Indian Roman and Kannada script (cf. Fig. 3(a)). However, it is not in the case of IAM database Roman and Kannada script (cf. Fig. 3(b)). This analysis highlights the impact of native writer's writing style while writing Roman script.

Fig. 4(a) illustrates bi-script classification accuracies, wherein we can notice the remarkable performance of D-DCT compared to conventional DCT. In addition, the time complexity difference between DDI and D-DCT in extracting features can be noticed in Fig. 4(b). Furthermore, to authenticate performance of the presented method that is D-DCT, we have extended our experiment on a dataset of 22,500 printed text words used in [5]. The classification results from multi-scripts in addition to Odiya ($\mathcal{O}$) script with LDA are presented in Table VII. The average identification result is 97.06%, which

TABLE VII. MULTI-SCRIPT IDENTIFICATION RESULTS OF PRINTED TEXT WORDS IN % WITH LDA.

Script	$\mathcal{R}$	$\mathcal{D}$	$\mathcal{K}$	$\mathcal{T}_{\mathcal{A}}$	$\mathcal{O}$	Average
D-DCT	94.13	97.71	99.82	95.22	98.44	97.06

Fig. 3. An example of features spread plot (a) horizontal features of Indian Roman and Kannada script, (b) horizontal features of IAM Roman and Kannada scrip, and (c) diagonal features of Indian Roman and Kannada script.

Fig. 4. It illustrates (a) script identification performance of conventional DCT and D-DCT, (b) time complexity (in sec.) of feature extraction methods (DDI and D-DCT).

is very high as compared to 93.5% and 96.0% reported with LDA and K -NN in [5]. The results of [5] is achieved by using 36 features; however, we achieved an accuracy of 97.06% by using only one-third features of [5] i.e., 12 features. In addition, it can be seen that diagonal features (*cf.* Fig. 3(c)) have induced high separability between features of Indian Roman and Kannada script as compared to horizontal features (*cf.* Fig. 3(a)). Thus, all the above facts and figures comprehend the novelty of D-DCT plus LDA scheme.

IV. CONCLUSION AND FUTURE WORK

In this paper, we have presented a technique of directional DCT for identifying script of handwritten text words. The novelty shown by the proposed technique in discriminating six major Indic scripts is significant. This method is based on visual perception perceived with the shapes of characters of Indic scripts, which are dominated by directional strokes. To capture these properties, we have directionally tuned the traditional DCT and achieved remarkable performance as compared to the earlier works. We have a plan to design a generalized framework to deal with all handwritten and printed Indic scripts identification task at word level. As a part of it, we are working on printed text of 11 Indic scripts used in [2] and preliminary results produced are encouraging.

REFERENCES

- [1] G. Rajput and A. H.B., "Handwritten script recognition using dct and wavelet features at block level," in *Int. J. of Computer App.*, (3):158–163, 2010.
- [2] P. B. Pati and A. G. Ramakrishnan, "Word level multi-script identification," *Patt. Recog. Lett.*, **29**(9):1218–1229, 2008.
- [3] V. Singhal, N. Navin, and D. Ghosh, "Script-based classification of hand-written text document in a multilingual environment," in *Proc. of Int. Workshop on Research Issues in Data Eng.*, 2003, pp. 47–54.
- [4] S. B. Moussa, A. Zahour, A. Benabdelhafid, and A. Alimi, "Fractal-based system for arabic/latin, printed/handwritten script identification," in *Proc. of Int. Conf. on Doc. Ana. and Recog.*, 2008, pp. 1–4.
- [5] P. B. Pati and A. Ramakrishnan, "Hvs inspired system for script identification in indian multi-script documents," in *Proc. of Int. Conf. on Doc. Ana. and Recog.*, 2006, pp. 380–389.
- [6] K. Bhardwaj, S. Chaudhury, and S. D. Roy, "An empirical intrinsic mode based characterization of indian scripts," in *Proc. of the workshop on Doc. Ana. and Recog.*, 2012, pp. 120–123.
- [7] K. Roy, A. Banerjee, and U. Pal, "A system for word-wise handwritten script identification for indian postal automation," in *Proc. of INDICON*, 2004, pp. 473–480.
- [8] K. Roy and U. Pal, "Word-wise hand-written script separation for indian postal automation," in *Proc. of Int. Workshop on Frontiers in Handwriting Recog.*, 2006, pp. 521–526.
- [9] M. Hangarge and B.V.Dhendra, "Offline handwritten script identification in document images," *Int. J. of Computer Applications*, **4**(6):1–5, 2008.
- [10] R. Sarkar, N. Das, S. Basu, M. Kundu, M. Nasipuri, and D. K. Basu, "Word level script identification from bangla and devanagiri handwritten texts mixed with roman script," *J. of Computing*, **2**(2):103–108, 2010.
- [11] B. Alireza, K. Malike, and S. Mehdi, "A novel framework for farsi and latin script identification and farsi handwritten digit recognition," *J. of Automatic Control*, **20**(1): 17–25, 2010.
- [12] L. Zhou, Y. Lu, and C. L. Tan, "Bangla/english script identification based on analysis of connected component profiles," in *Proc. of Int. Conf. on Doc. Ana. and Recog.*, 2006, pp. 243–254.
- [13] B. Dhendra and M. Hangarge, "Global and local features based handwritten text words and numerals script identification," in *Proc. of Int. Conf. on Computational Intell. and Multimedia App.*, 2007, pp. 471–475.
- [14] D. Ghosh, T. Dube, and A. P. Shivaprasad, "Script recognition a review," *IEEE Trans. on Patt. Ana. and Machine Intell.*, **32**(12):2142–2161, 2010.
- [15] D. Guru, M. Ravikumar, and B. H. Harish, "A review on offline handwritten script identification," in *Proc. of IJCA on National Conf. on Advanced Computing and Comm.*, 2012, pp. 13–16.
- [16] A. Belaïd, K. C. Santosh, and V. P. D'Andecy, "Handwritten and printed text separation in real document," in *Proc. of IAPR Conf. on Machine Vision App.*, 2013.
- [17] M. Hangarge, K. C. Santosh, S. Doddamani, and R. Pardeshi, "Statistical texture features based handwritten and printed text classification in south indian documents," in *Proc. of ICECIT*, 2013, pp. 215–221.
- [18] N. Otsu, "A threshold selection method from gray-level histograms," *IEEE Trans. on Patt. Ana. and Machine Intell.*, **9**(1):62–66, 1979.
- [19] E. Lam and J. Goodman, "A mathematical analysis of the dct coefficient distributions for images," *IEEE Trans. on Image Proces.*, **9**(10):1661–1666, 2000.