



# EnaS: a new software for neural population analysis in large scale spiking networks

Hassan Nasser, Selim Kraria, Bruno Cessac

## ► To cite this version:

Hassan Nasser, Selim Kraria, Bruno Cessac. EnaS: a new software for neural population analysis in large scale spiking networks. Twenty Second Annual Computational Neuroscience Meeting: CNS 2013, Jul 2013, Paris, France. 14 (Suppl 1), pp.P57, 2013. <hal-00842303>

HAL Id: hal-00842303

<https://hal.inria.fr/hal-00842303>

Submitted on 8 Jul 2013

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

POSTER PRESENTATION

Open Access


# EnaS: a new software for neural population analysis in large scale spiking networks

Hassan Nasser<sup>1\*</sup>, Selim Kraria<sup>2</sup>, Bruno Cessac<sup>1</sup>

From Twenty Second Annual Computational Neuroscience Meeting: CNS\*2013  
Paris, France. 13-18 July 2013

With the advent of new Multi-Electrode Arrays techniques (MEA), the simultaneous recording of the activity up to hundreds of neurons over a dense configuration supplies today a critical database to unravel the role of specific neural assemblies. Thus, the analysis of spike trains obtained from *in vivo* or *in vitro* experimental data requires suitable statistical models and computational tools.

The EnaS software [7], developed by our team, offers new computational methods of spike train statistics, based on Gibbs distributions (in its more general sense, including, but not limited, to the Maximal Entropy - MaxEnt) and taking into account time constraints in neural networks (such as memory effects). It also offers several statistical model choices, some of these models already used in the community (such GLM [6] and the conditional



**Figure 1** The GUI of EnaS. This page allows displaying a spike-train, showing the firing rates and configuring the binning value (sampling rate) of the data. It also allows selecting a subset of neurons and sorting the neurons with respect to their activity.

\* Correspondence: hassan.nasser@inria.fr

<sup>1</sup>Neuromathcomp, INRIA/UNSA, Sophia-Antipolis, France

Full list of author information is available at the end of the article

intensity models [5]), and some others developed by us ([1] and [2]), and allows a quantitative comparison between these models. It also offers a control of finite-size sampling effects inherent to empirical statistics.

EnaS allows large scale simulation thanks to our recent study [2] (hundreds of neurons) with spatio-temporal constraints. It's available as a Graphical User Interface in order to make the tools more accessible by non-programmers. Within EnaS framework, programmers are also allowed to implement new tools and integrate them with the existing modules. We featured EnaS with parallel processing on personal computers (using MPI) and on clusters (Using OpenMP).

#### Author details

<sup>1</sup>Neuromathcomp, INRIA/UNSA, Sophia-Antipolis, France. <sup>2</sup>Dream, INRIA, Sophia-Antipolis, France.

Published: 8 July 2013

#### References

1. Nasser H, Marre O, Cessac B: Spatio-temporal spike trains analysis for large scale networks using maximum entropy principle and Monte-Carlo method. [http://lanl.arxiv.org/abs/1209.3886].
2. Vasquez JC, Marre O, Palacio AD, Berry II MJ, Cessac B: Gibbs distribution analysis of temporal correlations structure in retina ganglion cells. *Journal of Physiology* 2012, **106(3-4)**:120-127.
3. Schneidman E, Berry MJ, Segev R, Bialek W: Weak pairwise correlations imply strongly correlated network states in a neural population. *Nature* 2006, **440(7087)**:1007-1012.
4. Pillow JW, Paninski L, Uzzell VJ, Simoncelli EP, Chichilnisky EJ: Prediction and decoding of retinal ganglion cell responses with a probabilistic spiking model. *J Neurosci* 2005, **25**:11003-11013.
5. Ahmadian A, Pillow JW, Paninski L: Efficient Markov Chain Monte Carlo Methods for Decoding Neural Spike Trains. *Neural Computation* 2001, **23**:46-96.
6. Event Neural Assembly Simulation. [http://enas.gforge.inria.fr].

doi:10.1186/1471-2202-14-S1-P57

Cite this article as: Nasser et al.: EnaS: a new software for neural population analysis in large scale spiking networks. *BMC Neuroscience* 2013 **14**(Suppl 1):P57.

Submit your next manuscript to BioMed Central and take full advantage of:

- Convenient online submission
- Thorough peer review
- No space constraints or color figure charges
- Immediate publication on acceptance
- Inclusion in PubMed, CAS, Scopus and Google Scholar
- Research which is freely available for redistribution

Submit your manuscript at  
www.biomedcentral.com/submit

