

An open question: How to solve efficiently 3D frictional contact problem?

Vincent Acary, Maurice Brémond

► **To cite this version:**

Vincent Acary, Maurice Brémond. An open question: How to solve efficiently 3D frictional contact problem?. Computational Contact Mechanics: Advances and Frontiers in Modeling Contact (14w5147), Feb 2014, Banff, Canada. 2014, <<https://www.birs.ca/events/2014/5-day-workshops/14w5147>>. <hal-01062771>

HAL Id: hal-01062771

<https://hal.inria.fr/hal-01062771>

Submitted on 10 Sep 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

An open question : How to solve efficiently 3D frictional contact problem ?

V. Acary*, M. Brémond*

In this talk, we want to discuss possible numerical solution procedures for the following discrete frictional contact problem [1]. Let $n_c \in \mathbb{N}$ be the number of contact points and $n \in \mathbb{N}$ the number of degree of freedom. Given a symmetric positive (semi-)definite matrix $M \in \mathbb{R}^{n \times n}$, a vector $f \in \mathbb{R}^n$, a matrix $H \in \mathbb{R}^{n \times m}$ with $m = 3n_c$, a vector $w \in \mathbb{R}^m$ and a vector of coefficients of friction $\mu \in \mathbb{R}^{n_c}$, find three vectors $v \in \mathbb{R}^n$, $u \in \mathbb{R}^m$ and $r \in \mathbb{R}^m$ such that

$$\begin{aligned} Mv &= Hr + f, & u &= H^\top v + w, & \hat{u} &= u + g(u), \\ K^* &\ni \hat{u} \perp r \in K, \end{aligned} \tag{1}$$

where $g(u)$ is a nonsmooth function and $K \subset \mathbb{R}^{3n_c}$ is a Cartesian product of second order cone in \mathbb{R}^3 . For each contact α , the unknown variables $u^\alpha \in \mathbb{R}^3$ (velocity or gap at the contact point) and $r^\alpha \in \mathbb{R}^3$ (reaction or impulse) are decomposed in a contact local frame $(O^\alpha, N^\alpha, T^\alpha)$ such that $u^\alpha = u_N^\alpha N^\alpha + u_T^\alpha$, $u_N^\alpha \in \mathbb{R}$, $u_T^\alpha \in \mathbb{R}^2$ and $r^\alpha = r_N^\alpha N^\alpha + r_T^\alpha$, $r_N^\alpha \in \mathbb{R}$, $r_T^\alpha \in \mathbb{R}^2$. The set K is the cartesian product of Coulomb's friction cone at each contact, that is

$$K = \prod_{\alpha=1 \dots n_c} K^\alpha = \prod_{\alpha=1 \dots n_c} \{r^\alpha, \|r_T^\alpha\| \leq \mu^\alpha |r_N^\alpha|\} \tag{2}$$

and K^* is dual. The function g is defined as $g(u) = [[\mu^\alpha \|u_T^\alpha\| |N^\alpha|]^\top, \alpha = 1 \dots n_c]^\top$.

This problem is at the heart of the simulation of mechanical systems with 3D Coulomb's friction and unilateral constraints. It might be the result of the time-discretization by event-capturing time-stepping methods or event-detecting (event-driven) techniques of dynamical systems with friction or the result of a space-discretization (by FEM for instance) of the quasi-static problems of frictional contact mechanics [2]. On the mathematical programming point of view, the problem appears as Second Order Cone Complementarity Problem (SOCCP). If the nonlinear part of the problem is neglected ($g(u) = 0$), the problem is an associated friction problem with dilatation, and by the way, is a gentle Second Order Cone Linear Complementarity Problem (SOCLCP) with a positive matrix $H^\top M^{-1} H$ (possibly semi-definite). When the non-associated character of the friction is taken into account through $g(u)$, the problem is non monotone and nonsmooth, and then very hard to solve efficiently.

In this talk we will recall a result for the problem in (1) which ensures that a solution exists [3]. In this framework, we will list several algorithms that have been previously developed for solving the SOCCP (1) mainly based variational inequality and nonsmooth equations reformulations. On one hand, we will show that algorithms based on Newton methods for nonsmooth equations solve quickly the problem when they succeed, but suffer from robustness issues mainly if the matrix H has not full rank. On the other hand, the iterative methods dedicated to solving variational inequalities are quite robust but with an extremely slow rate of convergence. To sum up, as far as we know there is no option that combines time efficiency and robustness. To try to answer to this question, we develop an open collection of discrete frictional contact problems called FCLIB <http://fclib.gforge.inria.fr> in order to offer a large library of problems to compare algorithms on a fair basis. In this work, this collection is solved with the software SICONOS and its component SICONOS/NUMERICS <http://siconos.gforge.inria.fr> .

References

- [1] V. Acary and B. Brogliato. *Numerical methods for nonsmooth dynamical systems. Applications in mechanics and electronics*. Lecture Notes in Applied and Computational Mechanics 35. Berlin: Springer. xxi, 525 p. , 2008.
- [2] V. Acary and F. Cadoux. *Recent Advances in Contact Mechanics, Stavroulakis, Georgios E. (Ed.)*, volume 56 of *Lecture Notes in Applied and Computational Mechanics*, chapter Applications of an existence result for the Coulomb friction problem. Springer Verlag, 2013.
- [3] V. Acary, F. Cadoux, C. Lemaréchal, and J. Malick. A formulation of the linear discrete Coulomb friction problem via convex optimization. *ZAMM - Journal of Applied Mathematics and Mechanics / Zeitschrift für Angewandte Mathematik und Mechanik*, 91(2):155–175, 2011.

*INRIA Grenoble Rhône-Alpes.