

# History-Preserving Bisimilarity for Higher-Dimensional Automata via Open Maps

Uli Fahrenberg, Axel Legay

► **To cite this version:**

Uli Fahrenberg, Axel Legay. History-Preserving Bisimilarity for Higher-Dimensional Automata via Open Maps. LICS 2013 - Twenty-Eighth Annual ACM/IEEE Symposium on Logic in Computer Science, Jun 2013, New Orleans, United States. <hal-01087933>

**HAL Id: hal-01087933**

**<https://hal.inria.fr/hal-01087933>**

Submitted on 27 Nov 2014

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# History-Preserving Bisimilarity for Higher-Dimensional Automata via Open Maps Extended Abstract

Uli Fahrenberg   Axel Legay  
Irisa / INRIA Rennes, France

One of the popular notions of equivalence for non-interleaving concurrent systems is *history-preserving bisimilarity* (*hp-bisimilarity*). *Higher-dimensional automata* (*HDA*) [6], [7] is a non-interleaving formalism for reasoning about behavior of concurrent systems, which provides a generalization (up to hp-bisimilarity) to “the main models of concurrency proposed in the literature” [8].

Using open maps [4], we can show that hp-bisimilarity for HDA has a characterization directly in terms of (higher-dimensional) *transitions* of the HDA, rather than in terms of runs as *e.g.* for Petri nets. Our results imply *decidability* of hp-bisimilarity for finite HDA. They also put hp-bisimilarity firmly into the open-maps framework of [4] and tighten the connections between bisimilarity and weak topological fibrations [1], [5].

A full version of this report is available as [3].

A *precubical set* is a graded set  $X = \{X_n\}_{n \in \mathbb{N}}$  together with mappings  $\delta_k^\nu : X_n \rightarrow X_{n-1}$ ,  $k = 1, \dots, n$ ,  $\nu = 0, 1$ , satisfying the *precubical identity*  $\delta_k^\nu \delta_\ell^\mu = \delta_{\ell-1}^\mu \delta_k^\nu$  for  $k < \ell$ . The mappings  $\delta_k^\nu$  are called *face maps*, and elements of  $X_n$  are called *n-cubes*. Faces  $\delta_k^0 x$  of an element  $x \in X$  are to be thought of as *lower faces*,  $\delta_k^1 x$  as *upper faces*. *Morphisms*  $f : X \rightarrow Y$  of precubical sets are graded mappings  $f = \{f_n : X_n \rightarrow Y_n\}_{n \in \mathbb{N}}$  which commute with the face maps:  $\delta_k^\nu \circ f_n = f_{n-1} \circ \delta_k^\nu$ . This defines a category  $\mathbf{pCub}$  of precubical sets and morphisms.

The category of *higher-dimensional automata* is the comma category  $\mathbf{HDA} = * \downarrow \mathbf{pCub}$  of *pointed precubical sets* and with morphisms which respect the point.

We say that a precubical set  $X$  is a *path object* if there is a (necessarily unique) sequence  $(x_1, \dots, x_m)$  of elements in  $X$  such that  $x_i \neq x_j$  for  $i \neq j$ ,

- for each  $x \in X$  there is  $j \in \{1, \dots, m\}$  for which  $x = \delta_{k_1}^{\nu_1} \dots \delta_{k_p}^{\nu_p} x_j$  for some indices  $\nu_1, \dots, \nu_p$  and a *unique* sequence  $k_1 < \dots < k_p$ , and
- for each  $j = 1, \dots, m-1$ , there is  $k \in \mathbb{N}$  for which  $x_j = \delta_k^0 x_{j+1}$  or  $x_{j+1} = \delta_k^1 x_j$ .

If  $X$  and  $Y$  are path objects with representations  $(x_1, \dots, x_m)$ ,  $(y_1, \dots, y_p)$ , then a morphism  $f : X \rightarrow Y$  is called a *path extension* if  $x_j = y_j$  for all  $j = 1, \dots, m$  (hence  $m \leq p$ ). The category  $\mathbf{HDP}$  of *higher-dimensional paths* (*HDP*) is the subcategory of  $\mathbf{HDA}$  which as objects has pointed path objects, and whose morphisms are generated by isomorphisms and

pointed path extensions.

Following [2], we say that a morphism in  $\mathbf{HDA}$  is *open* if it has the right lifting property with respect to  $\mathbf{HDP}$ , and that  $\mathbf{HDA}$   $X, Y$  are *bisimilar* if there is  $Z \in \mathbf{HDA}$  and a span of open maps  $X \leftarrow Z \rightarrow Y$  in  $\mathbf{HDA}$ . It can be shown [2] that  $X$  and  $Y$  are bisimilar iff  $n$ -cubes with matching lower faces can be matched; this is a straight-forward generalization of ordinary bisimulation for transition systems and appears hence to be rather badly suited for concurrent systems. We can, however, show that this bisimilarity is precisely hp-bisimilarity.

A *cube path* in a precubical set  $X$  is a morphism  $P \rightarrow X$  from a path object  $P$ . Using the notion of adjacency from [7], [8], we can define what it means for two cube paths to be *homotopic*, *i.e.* to represent the same execution up to concurrency. The *unfolding*  $\tilde{X}$  of a  $\mathbf{HDA}$   $X$  is then defined to be the set of homotopy classes of pointed cube paths in  $X$ . With suitable structure maps, this becomes a precubical set, indeed, a *higher-dimensional tree*.

The category of *HDA up to homotopy*  $\mathbf{HDA}_h$  has as objects  $\mathbf{HDA}$  and as morphisms pointed precubical morphisms  $f : \tilde{X} \rightarrow \tilde{Y}$  of unfoldings. Noting that any  $\mathbf{HDP}$  is isomorphic to its own unfolding, we have an embedding  $\mathbf{HDP} \hookrightarrow \mathbf{HDA}_h$ . We can then say that a morphism in  $\mathbf{HDA}_h$  is *homotopy open* if it has the right lifting property with respect to  $\mathbf{HDP}$  and define *homotopy bisimilarity* accordingly.

*Theorem.* Two  $\mathbf{HDA}$  are homotopy bisimilar iff they are hp-bisimilar [8], iff they are bisimilar.

Using an arrow category, we can easily extend the above considerations to the (more interesting) case of *labeled HDA*.

- [1] Jiří Adámek, Horst Herrlich, Jiří Rosický, and Walter Tholen. Weak factorization systems and topological functors. *Appl. Categ. Struct.*, 10(3):237–249, 2002.
- [2] Uli Fahrenberg. A category of higher-dimensional automata. In *FOS-SACS*, volume 3441 of *LNCS*, pages 187–201. Springer, 2005.
- [3] Uli Fahrenberg and Axel Legay. History-preserving bisimilarity for higher-dimensional automata via open maps. *CoRR*, abs/1209.4927, 2012. <http://arxiv.org/abs/1209.4927>.
- [4] André Joyal, Mogens Nielsen, and Glynn Winskel. Bisimulation from open maps. *Inf. Comp.*, 127(2):164–185, 1996.
- [5] Alexander Kurz and Jiří Rosický. Weak factorizations, fractions and homotopies. *Appl. Categ. Struct.*, 13(2):141–160, 2005.
- [6] Vaughan Pratt. Modeling concurrency with geometry. In *POPL*, pages 311–322. ACM Press, 1991.
- [7] Rob J. van Glabbeek. Bisimulations for higher dimensional automata. Email message, June 1991. <http://theory.stanford.edu/~rvg/hda>.
- [8] Rob J. van Glabbeek. On the expressiveness of higher dimensional automata. *Theor. Comput. Sci.*, 356(3):265–290, 2006.