Audio Inpainting, Source Separation, Audio Compression. All with a Unified Framework Based on NTF Model

Cagdas Bilen, Alexey Ozerov, Patrick Pérez

Audio Inpainting, Source Separation, Audio Compression All with a Unified Framework Based on NTF Model

Çağdaş Bilen*, **Alexey Ozerov*** and **Patrick Pérez**

Technicolor
cagdas.bilen, alexey.ozerov, patrick.perez@technicolor.com

Keywords: Audio Inpainting, Source Separation, Informed Source Separation (ISS), Compressive Sampling, Nonnegative Tensor Factorization (NTF)

We propose a general signal recovery algorithm, that can recover J audio source signals in time, $s^{\tau}_{jt}, j \in [\![1, J]\!], t \in [\![1, T]\!]$, given the quantized source samples, y^{τ}_{jt}, each observed on the support Ω^{τ}_{j} and the quantized mixture samples, $x^{\tau}_{t} = \sum_{j=1}^{J} s^{\tau}_{jt} + a^{\tau}_{t}$, observed on Ξ^{τ} with quantization noise a^{τ}_{t}. The sources are modelled in the short time Fourier transform (STFT) domain with a normal distribution ($s_{jfn} \sim \mathcal{N}_c(0, v_{jfn})$) where the variance tensor $\mathbf{V} = [v_{jfn}]_{j,f,n}$ has the following low-rank non-negative tensor factorization (NTF) structure [7], $v_{jfn} = \sum_{k=1}^{K} q_{jk}\, w_{fk} h_{nk}$. This model is parametrized by $\boldsymbol{\theta} = \{\mathbf{Q}, \mathbf{W}, \mathbf{H}\}$, with $\mathbf{Q} = [q_{jk}]_{j,k} \in \mathbb{R}_{+}^{J\times K}$, $\mathbf{W} = [w_{fk}]_{f,k} \in \mathbb{R}_{+}^{F\times K}$ and $\mathbf{H} = [h_{nk}]_{n,k} \in \mathbb{R}_{+}^{N\times K}$.

We propose to recover the source signals with a generalized expectation-maximization (GEM) algorithm [4] based on multiplicative update (MU) rules [5]. The Algorithm is briefly described in Algorithm 1. Using the proposed approach, it is possible to solve a number of existing and new problems in audio signal processing:

- **Audio inpainting**: It is possible to recover arbitrary time domain losses in audio signals for applications such as signal declipping. NTF model is used for the ***first time*** for the recovery of arbitrary time domain losses [3].
- **Joint audio inpainting and source separation**: It is possible to jointly perform audio inpainting and source separation to improve the performance of both tasks. Audio inpainting and source separation are performed jointly for the ***first time*** [1].
- **Compressed sampling-based informed source separation**: It is possible to recover the sources from their random samples and the mixture via compressive sampling-based informed source separation. This new ISS scheme uses a simple encoder that has properties of distributed coding [8, 6] and it competes with traditional ISS. The concept of distributed coding and of compressive sampling based scheme is introduced for the ***first time*** in the informed source separation problem [2].

The presentation and the poster will include various new results for the proposed algorihtm with comparisons to state of the art methods in the different problems discussed above.

* The first and second authors have contributed equally for this work.
This work was partially supported by ANR JCJC program MAD (ANR-14-CE27-0002).
This work is submitted for a lightning talk and a poster.

Algorithm 1 GEM algorithm for NTF model estimation. Details can be found in [1, 2, 3]

```
procedure ESTIMATESOURCES-NTF(Ξ^τ, x^τ, {y^τ_jt}_{j=1}^J, {Ω^τ_j}_{j=1}^J)
    Initialize non-negative Q, W, H randomly and apply any known prior on Q, W, H
    repeat
        Estimate sources (s_jfn), given Q, W, H, x^τ, Ξ^τ, {y^τ_jt}_{j=1}^J, {Ω^τ_j}_{j=1}^J with Wiener filtering
        Apply constraints in the time domain, and estimate posterior power spectra of the sources (P̃)
        Update Q, W, H given P̃ using MU rules
    until convergence criteria met
end procedure
```

References

[1] Bilen, Ç., A. Ozerov, and P. Pérez (2015a, October). Audio declipping via nonnegative matrix factorization. In *IEEE Workshop on Applications of Signal Processing to Audio and Acoustics*.

[2] Bilen, Ç., A. Ozerov, and P. Pérez (2015b, October). Compressive sampling-based informed source separation. In *IEEE Workshop on Applications of Signal Processing to Audio and Acoustics*.

[3] Bilen, Ç., A. Ozerov, and P. Pérez (2015c, August). Joint audio inpainting and source separation. In *International Conference on Latent Variable Analysis and Signal Separation*.

[4] Dempster, A., N. Laird, and D. Rubin. (1977). Maximum likelihood from incomplete data via the EM algorithm. *Journal of the Royal Statistical Society. Series B (Methodological) 39*, 1–38.

[5] Févotte, C., N. Bertin, and J. Durrieu (2009, March). Nonnegative matrix factorization with the Itakura-Saito divergence. With application to music analysis. *Neural Computation 21*(3), 793–830.

[6] Girod, B., A. Aaron, S. Rane, and D. Rebollo-Monedero (2005, January). Distributed video coding. *Proceedings of the IEEE 93*(1), 71 – 83.

[7] Ozerov, A., C. Févotte, R. Blouet, and J.-L. Durrieu (2011, May). Multichannel nonnegative tensor factorization with structured constraints for user-guided audio source separation. In *IEEE International Conference on Acoustics, Speech, and Signal Processing (ICASSP'11)*, Prague, pp. 257–260.

[8] Xiong, Z., A. Liveris, and S. Cheng (2004, September). Distributed source coding for sensor networks. *IEEE Signal Processing Magazine 21*(5), 80–94.