

Gossiping with interference in radio ring networks

Jean-Claude Bermond, Takako Kodate, Joseph Yu

► **To cite this version:**

Jean-Claude Bermond, Takako Kodate, Joseph Yu. Gossiping with interference in radio ring networks. 20th Anniversary of Japan Conference on Discrete and Computational Geometry, Graphs, and Games, Aug 2017, TOKYO, Japan. hal-01963492

HAL Id: hal-01963492

<https://hal.inria.fr/hal-01963492>

Submitted on 21 Dec 2018

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Gossiping with interference in radio ring networks

Jean-Claude Bermond*

COATI joint project CNRS-Inria-UNS, France,
jean-claude.bermond@inria.fr

Takako Kodate

Department of Information and Sciences,
Tokyo Woman's Christian University, Japan,
kodate@lab.twcu.ac.jp

Joseph Yu

Department of Mathematics,
University of the Fraser Valley, B.C., Canada,
joseph.yu@ufv.ca

1 Introduction

In this paper, we study the problem of gossiping with interference constraint in radio ring networks. Gossiping (or total exchange information) is a protocol where each node in the network has a message and wants to distribute its own message to every other node in the network. The gossiping problem consists in finding the minimum running time (makespan) of a gossiping protocol and efficient algorithms that attain this makespan.

Transmission model A radio network consists of communication devices equipped with an half duplex interface. The network is assumed to be synchronous and the time is slotted into *rounds*. The half-duplex hypothesis implies that a node can transmit or receive at most one message during a round. The network is modeled as a digraph, where the vertices represent the nodes and the arcs represent the possible communications. The messages are transmitted through the communication over the arcs and we will denote a call such a transmission.

Interference model We use a binary asymmetric model of interference based on the distance in the communication digraph like the ones used in [1, 2, 5]. Let $d(u, v)$ denote the distance, that is the length of a shortest directed path, from u to v in G and d_I be a non negative integer. We assume that when a node u transmits, all nodes v such that $d(u, v) \leq d_I$ are subject to the interference from u 's transmission. So two calls (u, v) and (u', v') do not interfere if $d(u, v') > d_I$ and $d(u', v) > d_I$.

This problem has been studied in [4] where approximation results are given (see also the survey [3]). Here we focus on the case where the transmission network is a ring network C_n on n nodes with the interference distance $d_I = 1$. We presented some partial results at JCDCG² 2013, and we have now solved completely the gossiping problem by giving the minimum running time (makespan). We show lower bounds and then give gossiping algorithms which meet these lower bounds and so are optimal.

*Funded by ANR STINT

2 Main Result

It appears that the determination of the minimum gossiping time needs various tools. The optimal time depends on the congruence of n modulo 12. Our results are summarized in the following theorem.

Theorem 1 *The minimum number of rounds R needed to achieve a gossiping in a ring network C_n ($n \geq 3$), with the interference model $d_I = 1$ is :*

$$\begin{cases} 2n - 3 & \text{if } n \equiv 0(\text{mod } 12) \\ 2n - 2 & \text{if } n \equiv 4, 8(\text{mod } 12) \\ 2n - 1 & \text{if } n \text{ is odd, except when } n = 3 \text{ for which } R = 3, \text{ and } n = 5 \text{ for which } R = 10 \\ 2n + 1 & \text{if } n \equiv 2, 6, 10(\text{mod } 12) \text{ except for } n = 6 \text{ for which } R = 12 \end{cases}$$

References

- [1] J.C. Bermond, R. Correa and M.L. Yu.: Optimal gathering protocols on paths under interference constraints, *Discrete Mathematics* 309: 5574–5587, 2009.
- [2] J.-C. Bermond, J. Galtier, R. Klasing, N. Morales, and S. Pérennes. Hardness and approximation of gathering in static radio networks. *Parallel Processing Letters*, 16(2): 165–183, 2006.
- [3] L. Gasieniec. On efficient gossiping in radio networks. Proc. Int. Conference on Theoretical Computer Science Colloquium on structural information and communication complexity, SIROCCO 2009, Lectures Notes in Computer science, springer Verlag, vol 5869: 2–14, 2010.
- [4] L. Gasieniec and I. Potapov. Gossiping with unit messages in known radio networks. Proc. 2nd IFIP Int. Conference on Theoretical Computer Science: 193–205, 2002.
- [5] R. Klasing, N. Morales, and S. Pérennes. On the complexity of bandwidth allocation in radio networks. *Theoretical Computer Science*, 406(3): 225–239, 2008.