



HAL
open science

Functional Connectivity for BCI: OpenViBE implementation

Arthur Desbois, Tiziana Cattai, Marie-Constance Corsi, Fabrizio de Vico
Fallani

► **To cite this version:**

Arthur Desbois, Tiziana Cattai, Marie-Constance Corsi, Fabrizio de Vico Fallani. Functional Connectivity for BCI: OpenViBE implementation. JJC-ICON'2021 - Journée Jeunes Chercheurs en Interfaces Cerveau-Ordinateur et Neurofeedback, CORTICO : Collectif pour la Recherche Transdisciplinaire sur les Interfaces Cerveau-Ordinateur, May 2021, Virtual, France. hal-03313685

HAL Id: hal-03313685

<https://hal.inria.fr/hal-03313685>

Submitted on 4 Aug 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Functional Connectivity for BCI: OpenViBE implementation

A. Desbois, T. Cattai, M.-C. Corsi, F. De Vico Fallani

*Inria, Aramis project-team, Paris Brain Institute – Institut du Cerveau (ICM), Inserm U 1127,
CNRS UMR 7225, Sorbonne Université, F-75013, Paris, France*

A possible way of interpreting electroencephalography (EEG) data is in terms of functional connectivity between channels, describing how brain areas mutually interact. Brain connectivity can be modeled as graphs, and mental states have been shown to be characterized by particular graph statistics (e.g. node strength or node efficiency) (1). Linking connectivity features to mental states can be a path to enhancing BCI performance.

OpenViBE is an open-source C++ based framework allowing real-time acquisition and processing of EEG data in a modular way, but algorithms and solutions for measuring and post-processing connectivity information are missing.

Based on previous works (3) , we implemented different connectivity algorithms in OpenViBE: magnitude squared coherence and imaginary part of coherence (2). We ensure low complexity by using the Eigen library (4) for algebraic operations, and implementing Welch's method (5) for computing the periodograms. We also developed matrix manipulation methods for post processing, and Graph Laplacian « denoising » (3).

We show this implementation is feasible for real-time Motor Imagery experimental protocols, as computing a single connectivity measure across 2 seconds of signal sampled at 512Hz, using 74 channels and 128 frequency bins takes less than 25ms on a typical workstation. When using 256 channels, this measure takes approximately 150ms, and 300ms when also using 256 frequency bins.

Research is currently ongoing to use functional connectivity as the basis for graph representation of the underlying brain networks, or with classification algorithms as an alternative feature to spectral power to discriminate between different Motor Imagery tasks: rest vs activity.

References

(1) J. Gonzalez-Astudillo, T. Cattai, G. Bassignana, M.-C. Corsi, and F. De Vico Fallani, "Network-based brain computer interfaces: principles and applications," *Journal of Neural Engineering*, 2020.

(2) Nolte & al (2004) "Identifying true brain interaction from EEG data using the imaginary part of coherency", *Clinical Neurophysiology* Volume 115, Issue 10, October 2004

(3) T.Cattai, G.Scarano, M.-C. Corsi et al - Improving J-divergence of brain connectivity states by graph Laplacian denoising - arXiv:2012.11240v2 [q-bio.NC]

(4) https://eigen.tuxfamily.org/index.php?title=Main_Page

(5) Welch, P.D. (1967) "The Use of Fast Fourier Transform for the Estimation of Power Spectra: A Method Based on Time Averaging Over Short, Modified Periodograms", IEEE Transactions on Audio Electroacoustics, AU-15, 70–73