



On Using Matching Theory to Understand P2P Network Design

Dmitry Lebedev, Fabien Mathieu, Laurent Viennot, Anh-Tuan Gai, Julien
Reynier, Fabien de Montgolfier

► To cite this version:

Dmitry Lebedev, Fabien Mathieu, Laurent Viennot, Anh-Tuan Gai, Julien Reynier, et al.. On Using Matching Theory to Understand P2P Network Design. [Research Report] RR-6075, INRIA. 2006, pp.7. inria-00121604v2

HAL Id: inria-00121604

<https://inria.hal.science/inria-00121604v2>

Submitted on 22 Dec 2006

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



INSTITUT NATIONAL DE RECHERCHE EN INFORMATIQUE ET EN AUTOMATIQUE

On Using Matching Theory to Understand P2P Network Design

Dmitry Lebedev — Fabien Mathieu — Laurent Viennot — Anh-Tuan Gai — Julien Reynier
— Fabien de Montgolfier

N° 6075

December 2006

Thème COM



*apport
de recherche*

On Using Matching Theory to Understand P2P Network Design

Dmitry Lebedev^{*}, Fabien Mathieu^{*}, Laurent Viennot[†], Anh-Tuan Gai[†], Julien Reynier[‡], Fabien de Montgolfier[§]

Thème COM — Systèmes communicants
Projets Gyroweb

Rapport de recherche n° 6075 — December 2006 — 7 pages

Abstract: This paper aims to provide insight into stability of collaboration choices in P2P networks. We study networks where exchanges between nodes are driven by the desire to receive the best service available. This is the case for most existing P2P networks. We explore an evolution model derived from *stable roommates* theory that accounts for heterogeneity between nodes. We show that most P2P applications can be modeled using stable matching theory. This is the case whenever preference lists can be deduced from the exchange policy. In many cases, the preferences lists are characterized by an interesting *acyclic* property. We show that P2P networks with acyclic preferences possess a unique stable state with good convergence properties.

Key-words: P2P networks, stable matchings, convergence properties

CRC MARDI

^{*} France Telecom R&D, 38–40, rue du général Leclerc, 92130 Issy les Moulineaux, France

[†] INRIA, domaine de Voluceaux, 78153 Le Chesnay cedex, France

[‡] LIENS, 45 rue d’Ulm, 75230 Paris Cedex 05, France

[§] LIAFA, 175, rue du Chevaleret, 75013 Paris France

Applications de la théorie des affectations à l'étude des réseaux P2P

Résumé : Cet article vise à décrire la possible stabilité d'un réseau pair-à-pair en termes de collaborations. Nous étudions les réseaux où les échanges entre pairs sont basés sur la volonté d'obtenir le meilleur service possible (hypothèse valable pour une grande partie des réseaux P2P existants). Nous considérons un modèle d'évolution basé sur la théorie des *stable roommates* afin de prendre en compte l'hétérogénéité des pairs. Nous montrons comment étudier la plupart des réseaux P2P à l'aide de ce modèle. Dans la plupart des cas rencontrés, le système de préférences sous-jacent possède une propriété d'acyclicité. Pour de tels systèmes, nous montrons l'existence d'une unique solution stable avec de bonnes propriétés de convergence.

Mots-clés : pair-à-pair, mariages stables, propriétés de convergence

1 Introduction

During the last few years, peer-to-peer (P2P) applications have emerged and now appear as a major component of the Internet, from both traffic and content distribution points of view. Peer-to-peer network performances scale reasonably with the number of users. This definitely makes P2P a leading paradigm for tomorrow's networking applications. One of the most striking achievements is certainly BitTorrent protocol [Coh03] for content distribution. It is based on a Tit-for-Tat mechanism, which is used to regularly compute collaboration links between the peers. Despite the simplicity of this approach, measurements and analysis are hard to provide due to the massively distributed nature of the applications. Starting from this statement, we present a formal method to analyze a large class of networks (including BitTorrent-like applications) with regard to the stability of collaborations.

More precisely, our main contribution is a model that fits any peer-to-peer protocol where peers are allowed to choose partners they are collaborating with. We just suppose that each peer ranks other peers according to some preference function. For example, in a P2P file-sharing network, each peer can rank other peers according to the similarity of their interest. In a cooperative download application such as BitTorrent [Coh03], the upload bandwidth appears as a major parameter as the incentive mechanism consists in selecting collaborators based on how much they upload. Additional parameters like download bandwidth, latency, storage capacity or even manual choices can also be used to define the preferences. Even though exact mechanisms of P2P solutions can be more complicated, our modeling gives a first approximation. In particular, it explains the evolution of a system where collaborators are selected according to such a parameter.

This work aims to deduce properties of the connection graph induced by the preference system chosen by a P2P application. The paper is structured as follows. In the next section, we present existing formal theories, namely the stable marriage problem [GS62] and the stable roommate problem [CF05]. In Section 3 we apply these theories to develop a model that includes many P2P applications. Section 4 identifies three main preference classes that appear in existing P2P applications. All of them appear to be cycle free and can be seen as particular cases of what we call acyclic preferences. In Section 5 we focus on acyclic preference systems and present a corresponding stability result. The convergence speed is discussed in Section 6.

2 Background: matching theory

Stable marriage problems were introduced by Gale and Shapley in 1962 [GS62]. An instance of the Stable Marriage problem involves two sets of participants, conveniently called the set of men M and the set of women W . A common assumption is that every member of each gender has strict preferences over the members of the opposite gender¹. The purpose of the theory is to find and describe the stable matchings (or configurations) between M and W . A matching \mathcal{M} is said to be unstable if there is a pair (m, w) where each one prefers being matched with the other rather than being in its current situation in \mathcal{M} . This pair is said to *block* the matching \mathcal{M} , and is called a blocking pair for \mathcal{M} . A stable matching is a matching with no blocking pair. Using a concept of *proposals*, Gale and Shapley have shown that all instances of the marriage problem possess at least one stable state that can be reached in $O(hf)$ proposals, where h is the number of men and f the number of women.

If there is only one set of participants (called *peers*), where anybody can be matched with anybody, then we get a different problem, called the Roommate problem. This change has two important consequences. Firstly, the existence of a stable configuration is no longer guaranteed, and secondly, a proposals algorithm like the Gale-Shapley algorithm may not converge, even if a stable configuration exists.

The first issue has been addressed by Irving in [Irv85]. The Irving algorithm finds a stable configuration to the roommates problem, if there is one, or it indicates that no solution exists. However, to the best of our knowledge, an adaptation of the Gale-Shapley algorithm to the roommates problem is still to be developed. One of the contributions of this work is a natural extension of Gale-Shapley to the stable roommates theory for the special case of acyclic preferences (see Section 5).

Finally, the roommates problem can be further generalized by allowing any peer p to establish a number $b(p)$ of simultaneous partnerships (instead of a single one as in the classical roommate matching problem). This generalization is often called many-to-many matching in the bipartite case or b -matching in the general case [Fle03, KU03]. Cechlárová and Fleiner [CF05] show how a b -matching problem can be transformed into an equivalent 1-matching problem. We propose to use b -matching to model the connections in a P2P network, as detailed in the following section.

¹The Stable Marriage with Ties problem (SMT) raises issues that will not be addressed in this paper. For existing studies on SMT, see [IMMM99, Man02].

3 Networks as matching instances

P2P networks are formed by establishing an overlay network between peers. Any peer acts both as a server and a client. Each peer p uses a bounded number of connections. As the network evolves, peers continuously seek after new (or better) partners. Each protocol implements its own algorithm for this searching phase. But in most of the cases, its output can be seen as a preference list over the contacts. Thus, a P2P protocol algorithm for connecting peers can be modeled as an instance of a b -matching problem.

As for the stable roommates problem, we consider a set P of n peers. All possible connections between the peers are defined by an *acceptance graph*. Each peer p has a *quota* $b(p)$ on the number of mates (connections). In addition, all neighbors of p from the acceptance graph are sorted according to a given preference system and form a preference list denoted by $L(p)$. $L(p, q)$ denotes the position (rank) of peer q in p 's list. In other terms, $L(p)$ is a permutation of all neighbors of p . If $L(p, q) < L(p, r)$ then we say that p *prefers* q to r . The best rank corresponds to 1. The *degree* of a peer is the length of its preference list. If we denote by L a vector of preference lists corresponding to all peers, then (P, L) (if there is no ambiguity P is omitted) defines an *instance* of the Roommates Problem.

For simplicity we consider only *undirected acceptance graphs*: $p \in L(q)$ iff $q \in L(p)$. There is no loss of generality since pairs are formed only between peers that mutually accept each other. Let m denote the number of edges of the acceptance graph.

When a partnership is established between two peers p and q , we say that each one is a *mate* of the other, or equivalently that the *pair* $\{p, q\}$ is formed. A *configuration* C is defined as a set of formed *pairs* $\{p, q\}$ such that each pair p has at most $b(p)$ mates. Some peers may be single (i.e. not paired). The set of all configurations is called \mathcal{C} . It contains the trivial configuration C_\emptyset , where no peer is paired.

In a configuration C , we say that p is *under-mated* if it has less than $b(p)$ mates in C . A *blocking pair* for a configuration C is a pair $\{p, q\} \notin C$ such that each member of the blocking pair is either under-mated or prefers the other to its worst mate in C .

We propose to model the evolution of the system through *initiatives*, a natural extension of the Gale-Shapley initiative algorithm [GS62]. An initiative is the process by which a peer may change its mates. Given a configuration C , we say that peer p *takes the initiative* when it proposes to other peers to be its new mate. Basically, p may propose partnership to any acceptable peer. However, a new partnership is only interesting when a blocking pair exists. If a peer p is part of a blocking pair (p, q) and elopes with q , the initiative is then called *active* because it modifies the configuration (both peers will change their set of mates).

To find such a new mate, p searches its preference list avoiding peers that do not improve its situation. We identify several strategies depending on how p searches its preference list:

- *best mate*: p seeks the best peer with which it forms a blocking pair.
- *decremental mate*: p circularly scans $L(p)$ starting from the position of the previous initiative.
- *random mate*: p chooses at random among the blocking pairs it belongs to.

Best mate seems to be the best strategy from a peer's point of view. However, when making proposals takes a valuable time, it may not be realistic. For this reason, we consider the two other types of initiative which are more suited to model simultaneous asynchronous initiatives. For instance, consider an application where peers are not aware of their neighbors' value. To try to find a better mate, a peer will select a random neighbor, probe it and keep collaborating with it if it is more interesting than some previous mate. This is the random mate strategy.

Let us now consider how preferences usually appear in P2P networks.

4 Acyclic networks

In this section, we show that most current P2P networks tend to conclude partnerships based on preferences which appear to be acyclic. A *preference cycle* between $k \geq 3$ peers $p_1 \dots p_k$ occurs if p_i prefers p_{i+1} to p_{i-1} (modulo k). A preference instance is *acyclic* if it contains no preference cycle.

First consider networks where mates are selected according to some inherent capacity like available bandwidth², computing capacity, or storage capacity. In such a system, a peer p possesses an intrinsic mark $m(p)$ acknowledged by all the peers it knows. Peers with higher marks are preferred. The preference lists resulting from such a policy are called *global preferences*. Consider a preference chain $p_1 \dots p_k$ where peer p_i prefers p_{i+1} to p_{i-1} . As marks increase along the chain, it cannot form a preference cycle, and global preferences are always acyclic.

As an example, consider the "Tit-for-Tat" strategy of BitTorrent [Coh03]. Each peer prefers to exchange with peers with the best upload capacity: as such peers provide data at a higher rate, they appear as best uploaders as soon as a

²Network available bandwidth often mainly depends on the type of the peer Internet connection and how much is consumed by other concurrent applications.

steady sequence of chunk exchanges is initiated. BitTorrent's Tit-for-Tat policy is thus close to a global preference system according to upload capacity. In addition to best uploaders, each peer also serves a random contact. This "generous" connection can be seen as a probing mechanism for finding mates with better upload capacity.

However, it should be noted that peer selection also relies on the complementarity of file chunks. This can be further modeled by a second type of preference system that we call *complementary preferences*. In such a system, all peers try to get the same set of resources (such as file chunks in cooperative file download). Each peer then prefers to exchange resources with peers possessing the largest number of its missing resources. It can be shown that such complementary preferences are also acyclic. Notice that this kind of preference changes as blocks are downloaded. However, the peers with the largest complementary set of blocks are those enabling the longest block exchange sessions. In its most general form, the selection of peers for cooperative file download can be seen as a mix of two acyclic preference systems.

Finally, we identify a third class of acyclic preference systems where each peer p gives a mark $m(p, q)$ to each peer q it knows in such a manner that marks are symmetric: $m(p, q) = m(q, p)$ for all p, q . Each peer prefers to pair with peers with the best marks. Such a preference system is said to be *symmetric*. Again the marks increase along a preference chain, preventing the existence of a preference cycle. The simplest example of such a preference system comes from latency optimization. Consider an overlay scheme such as Pastry [RD01] that is optimized by selecting contacts with the smallest round trip time (RTT) in the physical network. As the RTT is a symmetrical measure (on average), it results in symmetric marks.

In fact, any selection mechanism induced by proximity according to some distance function results in such symmetric preferences. For example, massively multiplayer online games (MMOG) require to connect players with nearby coordinates in a virtual space. This can be modeled by symmetric preferences based on distance in the virtual space. Similarly, some authors propose to connect participants of a file sharing system according to the similarity of their interest [FHKM04, SMZ03]. Any such preference system based on proximity is symmetric and thus acyclic.

We have seen that many P2P networks are formed through peer selection algorithms that can be modeled by preference instances that are acyclic. We now consider the stability properties of such preference systems.

5 Stability result

While it is difficult to find the stable solutions for general preferences in the roommates problem, the issue for acyclic preferences is much simpler, as shown by Theorem 1.

Theorem 1 *An acyclic b -matching preference instance always has a unique stable configuration.*

Proof: We first prove by contradiction that there can be at most one stable solution when preferences are acyclic. Suppose A and B are two distinct stable configurations of the instance. There exists a peer p_1 with different mates in A and B . Let p_2 be the best mate among the mates p_1 is matched with in A or B , but not in both configurations. Assume, without loss of generality, that p_1 is mated with p_2 in A , but not in B . As B is stable, p_2 has $b(p_2)$ mates in B it prefers to p_1 (otherwise $\{p_1, p_2\}$ would be a blocking pair for B). At least one of them is not its mate in A ; let p_3 be the best ranked. For a similar reason, p_3 has a mate p_4 in A and not in B it prefers to p_2 . We iterate the process to construct a sequence of peers $(p_i)_{i \geq 1}$. As the set of peers is finite, a peer p_k is found that is already present in the sequence. Let us take the smallest k such that $p_i = p_k$ for some $i < k$. The choice of p_{i+1} implies that p_i prefers p_{i+1} to p_{k-1} . By construction, the circular list p_i, p_2, \dots, p_{k-1} is a preference cycle. This contradicts the fact that the instance is acyclic.

To ensure the existence of a stable solution, we now prove that when preferences are acyclic, a sequence of active initiatives (i.e., initiatives that change the configuration) never goes twice through the same configuration. As there is a finite number of possible configurations, if we keep altering the configuration through initiatives, we eventually reach a configuration that cannot be altered with any initiative: a stable configuration.

The proof is simple. If a sequence of initiatives induces a cycle of at least two distinct configurations, then one can extract a preference cycle: let p_1 be a peer whose mates change through the cycle. Call p_2 the best peer p_1 is unstably paired with during the cycle, and p_3 the best peer p_2 is unstably paired with during the cycle. p_1 is not p_3 and p_2 prefers p_3 to p_1 , otherwise the pair $\{p_1, p_2\}$ would not break during the cycle. Iterating the process, we build a sequence of peer (p_k) such that p_k prefers p_{k+1} to p_{k-1} , until we find $i < j$ such that $p_i = p_j$. The circular list $(p_i, p_{i+1}, \dots, p_{j-1})$ is a preference cycle. \square

Theorem 1 can be also proved using Tan's decomposition theory [Tan91]. However, our proof has the advantage of leading to Corollary 1.

Corollary 1 *Any sufficiently long sequence of active initiatives leads to the unique stable configuration.*

Any initiative algorithm, starting from any configuration, computes the stable configuration if we assume it gives enough initiatives to active peers. This statement alone gives no guarantee on the convergence speed (except a factorial bound derived from the number of possible configurations), but more insight is given next.

6 Convergence results

In order to understand acyclic dynamics, we shall introduce the concept of loving pair. A loving pair $\{p, q\}$ is a pair of peers such that peer p is ranked first by peer q and *vice versa*. Loving pairs are the key to understanding acyclic preferences and convergence to the stable state. They have two main properties: first, loving pairs are unbreakable. Once peers of a loving pair are matched together, no sequence of initiatives can unmatched them. The second property is given by Theorem 2. An instance is said to be trivial when all preference lists are empty.

Theorem 2 *Any non-trivial acyclic preference instance always has at least one loving pair.*

Proof: Consider a non-trivial preference instance. There exist 2 peers p_0, p_1 such that $L(p_0, p_1) = 1$. If $L(p_1, p_0) = 1$, then $\{p_0, p_1\}$ is a loving pair. Otherwise, there exists $p_2 \neq p_0$ such that $L(p_1, p_2) = 1$. If we continue this process, we eventually find a loving pair p_i, p_{i+1} such that $L(p_i, p_{i+1}) = L(p_{i+1}, p_i) = 1$. If this is not the case, we construct a sequence p_0, \dots, p_i, \dots such that $L(p_{i-1}, p_i) = L(p_i, p_{i+1}) = 1$, with $p_{i-1} \neq p_{i+1}$. As the number of peers is finite, the sequence loops, producing a preference cycle. \square

Because of loving pairs, the stable solution can be constructed pair by pair through initiatives. This is stated in Theorem 3.

Theorem 3 *For any acyclic preferences instance, starting from any initial configuration C , there exists a sequence of at most $\frac{B}{2}$ initiatives leading to the stable solution, where $B = \sum_{p \in P} b(p)$.*

Proof: Theorem 1 guarantees that a stable configuration exists for any acyclic preference instance. We show that this stable state can be reached by matching loving pairs. We say that a pair is *stable* when no sequence of initiatives can break it. All stable pairs $\{p, q\}$ can be taken out of consideration: we can virtually remove them from the acceptance graph, erasing each peer from the preference list of the other, and decrementing the quotas $b(p)$ and $b(q)$. Similarly, a peer p that appears in $b(p)$ stable pairs will never change its mates, which is equivalent to considering a preference instance where p has been removed. In both cases, we obtain a smaller, but strictly equivalent preference instance. Moreover, this preference instance remains acyclic.

Starting from any configuration, we first remove all stable pairs and peers with a full quota of stable pairs as described above. The equivalent preference instance is acyclic. As long as it is non-trivial, Theorem 2 implies the existence of loving pairs. We give a best mate initiative to one peer of a loving pair. The loving pair is then formed and it is stable. We can remove it from consideration. It results in an equivalent preference instance where B is decremented by 2. If one of the peers has now a 0 quota, it can be removed from the preference instance. By iterating this process at most $\frac{B}{2}$ times, we end up in a configuration with a trivial equivalent preference instance where all preference lists are empty. This final configuration is thus the stable solution of the initial preference instance. \square

The above algorithm for computing an optimal initiative sequence is hard to implement in a massively distributed environment. However the key of Theorem 3 is that the stable solution is made of at most $B/2$ stable matchings, and that at each moment, one of them is a loving pair for the current configuration. With the best mate strategy, a loving pair is formed as soon as one of its peers has the initiative. We can estimate the convergence speed by estimating the time needed to match loving pairs. For instance, consider two simple random algorithms: periodic and Poisson.

In the periodic algorithm, each peer takes a best mate initiative every t seconds. Due to network latencies, we consider that the order of initiative may be different in each period. By Theorem 2, with *best mate*, a loving pair is formed after at most t seconds. Thus, in an acyclic preference instance, with periodic initiatives, the stable configuration is reached after at most $\frac{B}{2}t$ seconds.

In the Poisson algorithm, at any step a peer drawn uniformly at random with probability $\frac{1}{n}$ takes an initiative. A classical balls and bins result states that, with high probability (w.h.p.), each peer will have taken the initiative at least once after $n \log n$ drawings. Thus, in an acyclic preference instance, with best mate Poisson initiatives, the stable configuration is reached in $O(nB \log n)$ initiatives w.h.p..

The mean convergence time is much smaller. Considering that in each unstable configuration there exists at least 2 peers from a loving pair, the mean time between the creation of two stable pairs in a best mate Poisson initiatives sequence is at most $\frac{n}{2}$. As a consequence, for any acyclic instance and any starting configuration, the mean time to reach the stable state with best mate Poisson initiatives is at most $\frac{nB}{4}$.

7 Future Work and Conclusions

In the present work we have given upper bound estimates of the convergence time. These results are based on the existence of at least one loving pair at every step. Preliminary simulation results lead us to believe that the $\frac{nB}{4}$ bound on is tight for global preferences, when $b = 1$ and the acceptance graph is complete. In this case the only loving pair is composed of the two best globally ranked peers, which do not yet have paired together. However, we suspect that several other P2P networks preference systems, such as symmetric preferences, may contain a large number of loving pairs at a time. These systems should converge much faster. We plan to identify and analyze such preference systems.

Note, that our convergence results assume that the preference lists are static. However, for most P2P networks, the set of peers and their preference lists evolve in time. Further work will consider the impact of such dynamics on the stable configuration of the system. A major interest is to compare convergence speed to the system evolution speed. As long as it is fast enough, we can expect that the system will smoothly follow the evolving stable configuration target.

We have shown how collaboration selection algorithms can be modeled using the matching theory. In fact, most of these algorithms lead to acyclic preference instances and we have proved that such preference systems always evolve towards a stable configuration. Additional insight was given on the convergence time which is required to reach this stable configuration.

Acknowledgment: The authors wish to thank James Roberts for his helpful comments

References

- [CF05] K. Cechlárová and T. Fleiner. On a generalization of the stable roommates problem. *ACM Trans. Algorithms*, 1(1):143–156, 2005.
- [Coh03] B. Cohen. Incentives build robustness in bittorrent. In *P2PECON*, 2003.
- [FHKM04] F. Fessant, S. Handurukande, A. Kermarrec, and L. Massoulie. Clustering in peer-to-peer file sharing workloads. In *Proceedings of the 3rd International Workshop on Peer-to-Peer Systems (IPTPS)*, 2004.
- [Fle03] T. Fleiner. The stable b-matching polytope. *Mathematical Social Science*, 46(2):149–158, 2003.
- [GS62] D. Gale and L.S. Shapley. College admissions and the stability of marriage. *American Mathematical Monthly*, 69:9–15, 1962.
- [IMMM99] K. Iwama, S. Miyazaki, D. Manlove, and Y. Morita. Stable marriage with incomplete lists and ties. In *ICALP*, pages 443–452, 1999.
- [Irv85] R. Irving. An efficient algorithm for the stable roommates problem. *J. of Algorithms*, 6:577–595, 1985.
- [KU03] H. Konishi and M. Unver. Credible group-stability in many-to-many matching problems. Technical Report 570, Boston College Department of Economics, September 2003.
- [Man02] D. Manlove. The structure of stable marriage with indifference. *Dis. Appl. Math.*, 122:167–181, 2002.
- [RD01] A. Rowstron and P. Druschel. Pastry: Scalable, decentralized object location, and routing for large-scale peer-to-peer systems. *Lecture Notes in Computer Science*, 2218:329–??, 2001.
- [SMZ03] K. Sripanidkulchai, B. Maggs, and H. Zhang. Efficient content location using interest-based locality in peer-to-peer systems. In *INFOCOM*, 2003.
- [Tan91] Jimmy J. M. Tan. A necessary and sufficient condition for the existence of a complete stable matching. *J. Algorithms*, 12(1):154–178, 1991.



Unité de recherche INRIA Rocquencourt
Domaine de Voluceau - Rocquencourt - BP 105 - 78153 Le Chesnay Cedex (France)

Unité de recherche INRIA Futurs : Parc Club Orsay Université - ZAC des Vignes
4, rue Jacques Monod - 91893 ORSAY Cedex (France)

Unité de recherche INRIA Lorraine : LORIA, Technopôle de Nancy-Brabois - Campus scientifique
615, rue du Jardin Botanique - BP 101 - 54602 Villers-lès-Nancy Cedex (France)

Unité de recherche INRIA Rennes : IRISA, Campus universitaire de Beaulieu - 35042 Rennes Cedex (France)

Unité de recherche INRIA Rhône-Alpes : 655, avenue de l'Europe - 38334 Montbonnot Saint-Ismier (France)

Unité de recherche INRIA Sophia Antipolis : 2004, route des Lucioles - BP 93 - 06902 Sophia Antipolis Cedex (France)

Éditeur
INRIA - Domaine de Voluceau - Rocquencourt, BP 105 - 78153 Le Chesnay Cedex (France)
<http://www.inria.fr>
ISSN 0249-6399