

# Analysis of a stabilized finite element method for fluid flows through a porous interface

Alfonso Caiazzo, Miguel Angel Fernández, Vincent Martin

► **To cite this version:**

Alfonso Caiazzo, Miguel Angel Fernández, Vincent Martin. Analysis of a stabilized finite element method for fluid flows through a porous interface. *Applied Mathematics Letters*, Elsevier, 2011, 24 (12), pp.2124-2127. <10.1016/j.aml.2011.06.012>. <inria-00543014>

**HAL Id: inria-00543014**

**<https://hal.inria.fr/inria-00543014>**

Submitted on 5 Dec 2010

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

*Analysis of a stabilized finite element method for  
fluid flows through a porous interface*

Alfonso Caiazzo — Miguel A. Fernández — Vincent Martin

**N° 7475**

December 2010

Thème BIO



*Rapport  
de recherche*





## Analysis of a stabilized finite element method for fluid flows through a porous interface

Alfonso Caiazzo\* , Miguel A. Fernández† , Vincent Martin‡

Thème BIO — Systèmes biologiques  
Projet REO

Rapport de recherche n° 7475 — December 2010 — 8 pages

**Abstract:** This work is devoted to the numerical simulation of an incompressible fluid through a porous interface, modeled as a macroscopic *resistive interface term* in the Stokes equations. We improve the results reported in [*M2AN* **42**(6):961–990, 2008], by showing that the standard Pressure Stabilized Petrov-Galerkin (PSPG) finite element method is stable, and optimally convergent, without the need for controlling the pressure jump across the interface.

**Key-words:** Stokes equation, porous interface, stabilized finite element method.

\* INRIA, REO project-team and Weierstrass Institute, [a.caiazzo@gmail.com](mailto:a.caiazzo@gmail.com).

† INRIA, REO project-team, [Miguel.Fernandez@inria.fr](mailto:Miguel.Fernandez@inria.fr).

‡ UTC Compiègne and INRIA, REO project-team, [Vincent.Martin@utc.fr](mailto:Vincent.Martin@utc.fr).

## Analyse d'une méthode d'éléments finis stabilisée pour les écoulements à travers une interface poreuse

**Résumé :** Ce travail concerne la simulation numérique d'un fluide incompressible à travers une interface poreuse, modélisée par un terme d'interface résistif macroscopique dans les équations de Stokes. Nous améliorons les résultats de [*M2AN* **42**(6):961–990, 2008], en montrant que la méthode d'éléments finis stabilisée classique PSPG (Pressure Stabilized Petrov-Galerkin) est stable, et converge de façon optimale, sans contrôle additionnel sur le saut de pression à l'interface.

**Mots-clés :** Équation de Stokes, interface poreuse, méthode d'éléments finis stabilisée.

## 1 Introduction

We consider a regular domain  $\Omega \subset \mathbb{R}^d$ ,  $d = 2$  or  $3$ , and a porous interface defined by a hyperplane domain  $\Gamma \subset \mathbb{R}^{d-1}$ , dividing  $\Omega$  in two connected subdomains as  $\Omega = \Omega_1 \cup \Gamma \cup \Omega_2$ . We denote by  $\mathbf{n}_1, \mathbf{n}_2$  the outgoing normals from each subdomain  $\Omega_i$  at the interface, with  $\mathbf{n}_1 = -\mathbf{n}_2$ , and we define  $\mathbf{n} = \mathbf{n}_1$ . The fluid velocity  $\mathbf{u}$  and pressure  $p$  are governed by the following modified Stokes equations [3]:

$$\begin{aligned} \nabla p - \mu \Delta \mathbf{u} + r_\Gamma \delta_\Gamma \mathbf{u} &= \mathbf{f} & \text{in } \Omega, \\ \operatorname{div} \mathbf{u} &= 0 & \text{in } \Omega, \end{aligned} \quad (1)$$

with a homogeneous Dirichlet condition on  $\partial\Omega$ . In (1), the symbol  $\mu$  stands for the fluid viscosity,  $\mathbf{f}$  for a given volume force,  $\delta_\Gamma$  for the Dirac measure on  $\Gamma$ , and  $r_\Gamma > 0$  is a given interface resistance, related to the permeability and porosity of the interface. Without loss of generality,  $r_\Gamma$  is assumed to be a constant scalar.

Problem (1) can be reformulated equivalently as a two-domain Stokes problem, complemented with the interface conditions

$$[[\mathbf{u}]] = \mathbf{0}, \quad [[\mu \nabla \mathbf{u} \cdot \mathbf{n} - p\mathbf{n}]] = -r_\Gamma \mathbf{u} \quad \text{on } \Gamma, \quad (2)$$

where  $[[q]] \stackrel{\text{def}}{=} q_1|_\Gamma - q_2|_\Gamma$  denotes the jump across  $\Gamma$  and  $q_i \stackrel{\text{def}}{=} q|_{\Omega_i}$  ( $i = 1, 2$ ).

In [3], problem (1) was discretized with an extension of the PSPG stabilized method (see [4]): an additional consistent term (based on (2)) was introduced to control the interface pressure jump. Numerical evidence showed, however, that this term did not improve noticeably the behavior of the numerical solution with respect to a standard PSPG stabilized formulation [3]. The aim of this note is to show that, indeed, stability and optimal accuracy can be derived without the need for this extra interface stabilization term (which is convenient in practice).

## 2 Finite element formulation

Let  $\{\mathcal{T}_h\}_{0 < h \leq 1}$  be a regular family of quasi-uniform triangulations of  $\Omega$ , conforming with the interface  $\Gamma$ . The corresponding triangulation of the interface is denoted by  $\mathcal{G}_h$  and we set  $h \stackrel{\text{def}}{=} \max_{T \in \mathcal{T}_h} h_T$ , where  $h_T$  is the diameter of the element  $T$ . We introduce the spaces  $\mathbf{V} \stackrel{\text{def}}{=} [H_0^1(\Omega)]^d$ ,  $Q \stackrel{\text{def}}{=} L_0^2(\Omega)$ , and the finite element spaces of degree  $k \geq 1$ ,  $\mathbf{V}_h^k$  and  $N_h^k$ , equal order approximations of  $\mathbf{V}$  and  $Q$ :

$$\begin{aligned} \mathbf{V}_h^k &\stackrel{\text{def}}{=} \{ \mathbf{v}_h \in (\mathcal{C}^0(\bar{\Omega}))^d \mid \mathbf{v}_h|_T \in (\mathbb{P}_k)^d \ \forall T \in \mathcal{T}_h \} \cap \mathbf{V}, \\ N_h^k &\stackrel{\text{def}}{=} \{ q_h|_{\Omega_i} \in \mathcal{C}^0(\bar{\Omega}_i), \ i = 1, 2 \mid q_h|_T \in \mathbb{P}_k \ \forall T \in \mathcal{T}_h \} \cap Q. \end{aligned} \quad (3)$$

Note that the space  $N_h^k$  of discrete pressures allows discontinuity at the interface  $\Gamma$ . As underlined in [3], this is of utmost importance to get a correct approximation of the solution without excessive mesh refinement. Additionally, we introduce the spaces  $\mathbf{V}_0 \stackrel{\text{def}}{=} \{ \mathbf{v} \in \mathbf{V} \mid \mathbf{v}|_\Gamma = \mathbf{0} \}$  and  $\mathbf{V}_{0,h}^k \stackrel{\text{def}}{=} \mathbf{V}_0 \cap \mathbf{V}_h^k$ .

Let us consider the two following bilinear forms

$$\begin{aligned} \mathcal{A}_\delta^{r_\Gamma}(\mathbf{x}_h, \mathbf{y}_h) &\stackrel{\text{def}}{=} (\mu \nabla \mathbf{u}_h, \nabla \mathbf{v}_h) - (p_h, \operatorname{div} \mathbf{v}_h) + (r_\Gamma \mathbf{u}_h, \mathbf{v}_h)_\Gamma + (\operatorname{div} \mathbf{u}_h, q_h) \\ &\quad + \delta \sum_{T \in \mathcal{T}_h} \frac{h_T^2}{\mu} (\mu \Delta \mathbf{u}_h + \nabla p_h, \nabla q_h)_T, \\ \mathcal{B}_\delta^{r_\Gamma}(\mathbf{x}_h, \mathbf{y}_h) &\stackrel{\text{def}}{=} \mathcal{A}_\delta^{r_\Gamma}(\mathbf{x}_h, \mathbf{y}_h) - \delta \sum_{E \in \mathcal{G}_h} \frac{h_E}{\mu} (\llbracket \mu \nabla \mathbf{u}_h \cdot \mathbf{n} - p_h \mathbf{n} \rrbracket + r_\Gamma \mathbf{u}_h, \llbracket q_h \mathbf{n} \rrbracket)_E \end{aligned}$$

for all  $\mathbf{x}_h = (\mathbf{u}_h, p_h)$  and  $\mathbf{y}_h = (\mathbf{v}_h, q_h)$  in  $\mathbf{V}_h^k \times N_h^k$  and  $\delta > 0$  is a stabilization parameter. The discrete formulation proposed and analyzed in [3] is based on  $\mathcal{B}_\delta^{r_\Gamma}$ . In this note, we consider the numerical analysis of the standard PSPG formulation

$$\mathcal{A}_\delta^{r_\Gamma}(\mathbf{x}_h, \mathbf{y}_h) = (\mathbf{f}, \mathbf{v}_h) \quad \forall \mathbf{y}_h \in \mathbf{V}_h^k \times N_h^k. \quad (4)$$

### 3 Stability analysis

Let us consider the mesh-dependent energy norm

$$\|(\mathbf{u}_h, p_h)\|_h^2 \stackrel{\text{def}}{=} \mu \|\nabla \mathbf{u}_h\|_{0,\Omega}^2 + r_\Gamma \|\mathbf{u}_h\|_{0,\Gamma}^2 + \delta \sum_{T \in \mathcal{T}_h} \frac{h_T^2}{\mu} \|\nabla p_h\|_{0,T}^2 + \frac{1}{\mu} \|p_h\|_{0,\Omega}^2.$$

Note that, unlike in [3], this norm provides no control on the interface pressure jump. We address now the stability of (4) in the  $\|\cdot\|_h$  norm.

By applying the inverse inequality (see [1])

$$\|\Delta \mathbf{v}_h\|_{0,T} \leq c_\Delta h^{-1} \|\nabla \mathbf{v}_h\|_{0,T}, \quad \mathbf{v}_h \in \mathbf{V}_h^k,$$

and the Schwarz and Young inequalities to the term  $\sum_{T \in \mathcal{T}_h} h_T^2 (\Delta \mathbf{u}_h, \nabla p_h)_T$ , we get the following coercivity estimate.

**Proposition 3.1** *Let  $\delta$  be such that  $0 < \delta c_\Delta^2 \leq 1$ . Then*

$$\mathcal{A}_\delta^{r_\Gamma}(\mathbf{x}_h, \mathbf{x}_h) \geq \frac{\mu}{2} \|\nabla \mathbf{u}_h\|_{0,\Omega}^2 + r_\Gamma \|\mathbf{u}_h\|_{0,\Gamma}^2 + \frac{\xi^2}{2} \geq \frac{1}{2} \left( \|(\mathbf{u}_h, p_h)\|_h^2 - \frac{1}{\mu} \|p_h\|_{0,\Omega}^2 \right) \quad (5)$$

for all  $\mathbf{x}_h = (\mathbf{u}_h, p_h) \in \mathbf{V}_h^k \times Q_h^k$ , with  $\xi^2 \stackrel{\text{def}}{=} \delta \sum_{T \in \mathcal{T}_h} \frac{h_T^2}{\mu} \|\nabla p_h\|_{0,T}^2$ .

The stability and the optimal convergence are stated in the following result.

**Proposition 3.2** *Under the assumption of Proposition 3.1 there holds:*

(i) *there exists a constant  $\beta = \beta(\delta, \frac{\mu}{r_\Gamma})$  independent of  $h$ , such that*

$$\inf_{\mathbf{x}_h \in \mathbf{V}_h^k \times Q_h^k} \sup_{\mathbf{y}_h \in \mathbf{V}_h^k \times Q_h^k} \frac{\mathcal{A}_\delta^{r_\Gamma}(\mathbf{x}_h, \mathbf{y}_h)}{\|\mathbf{x}_h\|_h \|\mathbf{y}_h\|_h} \geq \beta. \quad (6)$$

Moreover, if  $\delta \ll 1$  we have  $\beta \sim \delta$ , and  $\beta = \mathcal{O}(\mu/r_\Gamma)$  for  $r_\Gamma/\mu \gg 1$ ;

(ii) let  $(\mathbf{u}_h, p_h)$  be the solution of (4) and assume that  $(\mathbf{u}, p)$ , the solution of (1), is such that  $\mathbf{u}_i \in [H^{k+1}(\Omega_i)]^d$ ,  $p_i \in H^k(\Omega_i)$ ,  $i = 1, 2$ . The following estimate holds

$$\|(\mathbf{u} - \mathbf{u}_h, p - p_h)\|_h \leq c h^k \sum_{i=1,2} \left( \|\mathbf{u}\|_{k+1,\Omega_i} + \|p\|_{k,\Omega_i} \right), \quad (7)$$

where  $c = c(r_\Gamma, \delta, \mu)$  is a positive constant, independent of  $h$ .

We remark that the stability and convergence results are essentially the same as the ones given in [3], but without the need for the extra stabilization term. The *inf-sup* constant  $\beta$  has also the same asymptotic behavior.

*Proof.* For the sake of conciseness, we prove only point (i). The proof of (ii) follows [3], owing to the stability of  $\mathcal{A}_\delta^{r\Gamma}$ . Let  $\mathbf{x}_h = (\mathbf{u}_h, p_h) \in \mathbf{V}_h^k \times N_h^k$ . Given (5), the *inf-sup* stability of  $\mathcal{A}_\delta^{r\Gamma}$  requires additional stability estimates needed to control the pressure.

A pressure  $p \in L_0^2(\Omega)$  has zero mean in  $\Omega$ , but this is not true in general for its restriction to  $\Omega_i$ ,  $i = 1, 2$ . Following an argument of [2], we decompose  $p_h \in N_h^k \subset L_0^2(\Omega)$  as  $p_h = p_h^0 + \bar{p}_h$ , with  $p_{h,i}^0 \in L_0^2(\Omega_i)$  and  $\bar{p}_{h,i} \stackrel{\text{def}}{=} (p_{h,i}, 1)_{\Omega_i}$  (i.e.,  $p_h^0$  has zero mean over each subdomain and  $\bar{p}_h$  is constant in each subdomain). The following relations hold:

$$\begin{aligned} \|p_h\|_{0,\Omega}^2 &= \|p_h^0\|_{0,\Omega}^2 + \|\bar{p}_h\|_{0,\Omega}^2, \\ \bar{p}_{h,1}|\Omega_1| + \bar{p}_{h,2}|\Omega_2| &= 0, \\ \|\bar{p}_h\|_{0,\Omega}^2 &= \bar{p}_{h,1}^2|\Omega_1| + \bar{p}_{h,2}^2|\Omega_2|. \end{aligned} \quad (8)$$

We show how to control separately  $p_h^0$  and  $\bar{p}_h$ . Since  $p_{h,i}^0 \in L_0^2(\Omega_i)$ ,  $i = 1, 2$ , there exists a function  $\mathbf{v}^0 \in \mathbf{V}_0$ , such that  $\mathbf{v}_i^0 \in [H_0^1(\Omega_i)]^d$ ,  $-\text{div } \mathbf{v}_i^0 = p_{h,i}^0$  and  $\|\mathbf{v}^0\|_{1,\Omega} \leq c_\Omega \|p_h^0\|_{0,\Omega}$ . We take  $\mathbf{v}_h^0$  as the Scott-Zhang interpolant of  $\mathbf{v}^0$  into  $\mathbf{V}_{0,h}^k$ , defined separately on each subdomain. Using the properties of the Scott-Zhang operator [1], we also have  $\|\mathbf{v}_h^0\|_{1,\Omega} \leq c'_\Omega \|p_h^0\|_{0,\Omega}$  and  $\|\mathbf{v}^0 - \mathbf{v}_h^0\|_{0,\Omega} \leq c_\pi h \|\mathbf{v}^0\|_{1,\Omega}$ . Since  $\mathbf{v}_i^0, \mathbf{v}_{i,h}^0 \in [H_0^1(\Omega_i)]^d$ ,  $i = 1, 2$ , and  $\bar{p}_h$  is constant on each subdomain, we have  $(\mathbf{v}^0 - \mathbf{v}_h^0)|_\Gamma = 0$ ,  $(\bar{p}_h, \text{div } \mathbf{v}_h^0) = 0$  and  $(\bar{p}_h, \text{div } \mathbf{v}^0) = 0$ . Hence, using the fact that  $p_h \in N_h^k$  is continuous in  $\Omega_1$  and  $\Omega_2$  we obtain, integrating by parts in each subdomain:

$$\begin{aligned} -(p_h, \text{div } \mathbf{v}_h^0) &= -(p_h^0, \text{div } \mathbf{v}^0) + (p_h^0, \text{div}(\mathbf{v}^0 - \mathbf{v}_h^0)) \\ &\geq \|p_h^0\|_{0,\Omega}^2 - \xi c_\pi c_\Omega \delta^{-\frac{1}{2}} \mu^{\frac{1}{2}} \|p_h^0\|_{0,\Omega}, \end{aligned}$$

with  $\xi$  defined in Proposition 3.1. Using Young's inequality, this yields

$$\begin{aligned} \mathcal{A}_\delta^{r\Gamma}(\mathbf{x}_h, (\mathbf{v}_h^0, 0)) &\geq -c'_\Omega \mu \|\nabla \mathbf{u}_h\|_{0,\Omega} \|p_h^0\|_{0,\Omega} - \left(\frac{\mu}{\delta}\right)^{\frac{1}{2}} c_\pi c_\Omega \xi \|p_h^0\|_{0,\Omega} + \|p_h^0\|_{0,\Omega}^2 \\ &\geq \frac{1}{2} \|p_h^0\|_{0,\Omega}^2 - (c'_\Omega)^2 \mu^2 \|\nabla \mathbf{u}_h\|_{0,\Omega}^2 - \frac{\mu}{\delta} c_\pi^2 c_\Omega^2 \xi^2. \end{aligned} \quad (9)$$

To handle the constant part of the pressure, we need the following Lemma (whose proof can be found in [2] in a more complex case):



**Lemma 3.1** *There exist two (non-constant) functions  $\bar{\mathbf{v}}_h^\alpha \in \mathbf{V}_h^1$ ,  $\alpha = 1, 2$ , defined over the whole domain  $\Omega$  such that*

$$\|\nabla \bar{\mathbf{v}}_h^\alpha\|_{0,\Omega} + \|\bar{\mathbf{v}}_h^\alpha\|_{0,\Gamma} \leq \bar{c} \|\bar{p}_{h,\alpha}\|_{0,\Omega_\alpha}, \quad \int_\Gamma \bar{\mathbf{v}}_{h,1}^\alpha \cdot \mathbf{n}_1 = - \int_\Gamma \bar{\mathbf{v}}_{h,2}^\alpha \cdot \mathbf{n}_2 = \bar{p}_{h,\alpha} |\Omega_\alpha|.$$

Let  $\bar{\mathbf{v}}_h \stackrel{\text{def}}{=} \bar{\mathbf{v}}_h^2 - \bar{\mathbf{v}}_h^1 \in \mathbf{V}_h^k$ . Since  $\nabla \bar{p}_{h,i} = 0$  and using (8) and Lemma 3.1, we have

$$\begin{aligned} -(\bar{p}_h, \operatorname{div} \bar{\mathbf{v}}_h) &= \sum_{i=1,2} (\bar{p}_{h,i}, (\bar{\mathbf{v}}_h^1 - \bar{\mathbf{v}}_h^2) \cdot \mathbf{n}_i)_\Gamma \\ &= \bar{p}_{h,1}^2 |\Omega_1| - \bar{p}_{h,1} \bar{p}_{h,2} (|\Omega_2| + |\Omega_1|) + \bar{p}_{h,2}^2 |\Omega_2| \\ &= 2(\bar{p}_1^2 |\Omega_1| + \bar{p}_2^2 |\Omega_2|) = 2\|\bar{p}_h\|_{0,\Omega}^2, \end{aligned}$$

and, by applying Lemma 3.1 once more, there follows

$$\begin{aligned} -(p_h, \operatorname{div} \bar{\mathbf{v}}_h) &= -(\bar{p}_h, \operatorname{div} \bar{\mathbf{v}}_h) - (\bar{p}_h^0, \operatorname{div} \bar{\mathbf{v}}_h) \\ &\geq 2\|\bar{p}_h\|_{0,\Omega}^2 - \|p_h^0\|_{0,\Omega} d^{\frac{1}{2}} \|\nabla(\bar{\mathbf{v}}_h^1 - \bar{\mathbf{v}}_h^2)\|_{0,\Omega} \\ &\geq 2\|\bar{p}_h\|_{0,\Omega}^2 - d\bar{c}^2 \|p_h^0\|_{0,\Omega}^2 - \frac{1}{4} \left( \|\bar{p}_{h,1}\|_{0,\Omega_1} + \|\bar{p}_{h,2}\|_{0,\Omega_2} \right)^2 \\ &\geq \|\bar{p}_h\|_{0,\Omega}^2 - d\bar{c}^2 \|p_h^0\|_{0,\Omega}^2, \end{aligned}$$

where we recall that  $d$  denotes the spatial dimension. Hence,

$$\begin{aligned} \mathcal{A}_\delta^{r_\Gamma}(\mathbf{x}_h, (\bar{\mathbf{v}}_h, 0)) &\geq -2\mu\bar{c} \|\nabla \mathbf{u}_h\|_{0,\Omega} \|\bar{p}_h\|_{0,\Omega} - 2r_\Gamma \bar{c} \|\mathbf{u}_h\|_{0,\Gamma} \|\bar{p}_h\|_{0,\Omega} \\ &\quad + \|\bar{p}_h\|_{0,\Omega}^2 - d\bar{c}^2 \|p_h^0\|_{0,\Omega}^2 \\ &\geq \frac{1}{2} \|\bar{p}_h\|_{0,\Omega}^2 - d\bar{c}^2 \|p_h^0\|_{0,\Omega}^2 - 4\bar{c}^2 \mu^2 \|\nabla \mathbf{u}_h\|_{0,\Omega}^2 - 4\bar{c}^2 r_\Gamma^2 \|\mathbf{u}_h\|_{0,\Gamma}^2. \end{aligned} \tag{10}$$

Therefore, by taking  $\mathbf{y}_h = (\lambda \mathbf{v}_h^0 + (1-\lambda)\bar{\mathbf{v}}_h, 0)$ , with  $\lambda \stackrel{\text{def}}{=} \frac{1+2d\bar{c}^2}{2(1+d\bar{c}^2)} \in (0, 1)$ , and using (9) and (10), we obtain

$$\begin{aligned} \mathcal{A}_\delta^{r_\Gamma}(\mathbf{x}_h, \mathbf{y}_h) &\geq \left( \frac{\lambda}{2} - (1-\lambda)d\bar{c}^2 \right) \|p_h^0\|_{0,\Omega}^2 + \frac{1-\lambda}{2} \|\bar{p}_h\|_{0,\Omega}^2 \\ &\quad - \mu (\lambda(c'_\Omega)^2 + (1-\lambda)4\bar{c}^2) \|\nabla \mathbf{u}_h\|_{0,\Omega}^2 \\ &\quad - \frac{\mu}{\delta} \lambda c_\pi^2 c_\Omega^2 \xi^2 - (1-\lambda)4\bar{c}^2 r_\Gamma^2 \|\mathbf{u}_h\|_{0,\Gamma}^2 \\ &\geq \frac{1}{4\bar{c}} \|p_h\|_{0,\Omega}^2 - \mu c_{\max}^2 \left( \|\mathbf{u}_h, p_h\|_h^2 - \frac{1}{\mu} \|p_h\|_{0,\Omega}^2 \right), \end{aligned} \tag{11}$$

where we have introduced  $\bar{c} \stackrel{\text{def}}{=} 1+d\bar{c}^2$ , and  $c_{\max}^2 \stackrel{\text{def}}{=} \max \left\{ (c'_\Omega)^2 + 4\bar{c}^2, \frac{1}{\delta} c_\pi^2 c_\Omega^2, 4\bar{c}^2 \frac{r_\Gamma}{\mu} \right\}$ . Equation (11) provides a control on the pressure. To conclude the proof, we

take a test function  $\mathbf{z}_h \stackrel{\text{def}}{=} (1 - \omega)\mathbf{x}_h + \omega\mathbf{y}_h$ , with  $\omega \stackrel{\text{def}}{=} \frac{2\tilde{c}}{\mu + 2\tilde{c}(1 + 2\mu c_{\max}^2)} \in (0, 1)$ , and apply (5) and (11), to obtain

$$\begin{aligned} \mathcal{A}_\delta^{\Gamma}(\mathbf{x}_h, \mathbf{z}_h) &\geq \frac{1}{2}(1 - \omega) \left( \|(\mathbf{u}_h, p_h)\|_h^2 - \frac{1}{\mu} \|p_h\|_{0,\Omega}^2 \right) \\ &\quad + \omega \left( \frac{1}{4\tilde{c}} \|p_h\|_{0,\Omega}^2 - \mu c_{\max}^2 \left( \|(\mathbf{u}_h, p_h)\|_h^2 - \frac{1}{\mu} \|p_h\|_{0,\Omega}^2 \right) \right) \\ &\geq \left( \frac{1 - \omega}{2} - \omega \mu c_{\max}^2 \right) \left( \mu \|\nabla \mathbf{u}_h\|_{0,\Omega}^2 + r_\Gamma \|\mathbf{u}_h\|_{0,\Gamma}^2 + \xi^2 \right) + \frac{\omega}{4\tilde{c}} \|p_h\|_{0,\Omega}^2 \\ &\geq \frac{\mu}{2(\mu + 2\tilde{c}(1 + 2\mu c_{\max}^2))} \|\mathbf{x}_h\|_h^2. \end{aligned} \tag{12}$$

Moreover, it can be shown that  $\mathbf{z}_h$  can be controlled by  $\mathbf{x}_h$  as

$$\begin{aligned} \|\mathbf{z}_h\|_h &\leq (1 - \omega) \|\mathbf{x}_h\|_h + \omega \left( \|(\mathbf{v}_h^0, 0)\|_h + \|(\bar{\mathbf{v}}_h^1, 0)\|_h + \|(\bar{\mathbf{v}}_h^2, 0)\|_h \right) \\ &\leq (1 - \omega) \|\mathbf{x}_h\|_h + \omega \mu^{\frac{1}{2}} c'_\Omega \|p_h\|_{0,\Omega} + \omega \sqrt{2\tilde{c}} (\mu + r_\Gamma)^{\frac{1}{2}} \|\bar{p}_h\|_{0,\Omega} \\ &\leq (1 - \omega) \|\mathbf{x}_h\|_h + \omega \mu \sqrt{2} c_{\max} \|\mathbf{x}_h\|_h \\ &\leq \left( 1 - \omega + \omega \mu \sqrt{2} c_{\max} \right) \|\mathbf{x}_h\|_h \\ &\leq \mu \frac{1 + 2\tilde{c}c_{\max}(2c_{\max} + \sqrt{2})}{\mu + 2\tilde{c}(1 + 2\mu c_{\max}^2)} \|\mathbf{x}_h\|_h. \end{aligned} \tag{13}$$

Combining (12) and (13) we obtain that the global inf-sup condition (6) follows with a constant

$$\beta \stackrel{\text{def}}{=} \frac{1}{2(1 + 2\tilde{c}c_{\max}(2c_{\max} + \sqrt{2}))}.$$

The stated asymptotic behavior of  $\beta$  follows from the definition of  $c_{\max}$ .  $\square$

## References

- [1] S. C. Brenner and L. R. Scott. *The mathematical theory of finite element methods*. Springer Verlag, 2002.
- [2] Erik Burman and Peter Hansbo. A unified stabilized method for Stokes' and Darcy's equations. *J. Comput. Appl. Math.*, 198(1):35–51, 2007.
- [3] M. A. Fernández, J.-F. Gerbeau, and V. Martin. Numerical simulation of blood flows through a porous interface. *Math. Model. Num. Anal. (M2AN)*, 42(6):961–990, 2008.
- [4] T.J.R. Hughes, L.P. Franca, and M. Balestra. A new finite element formulation for computational fluid dynamics. V. Circumventing the Babuška-Brezzi condition: a stable Petrov-Galerkin formulation of the Stokes problem accommodating equal-order interpolations. *Comput. Methods Appl. Mech. Engrg.*, 59(1):85–99, 1986.

## Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>Finite element formulation</b>	<b>3</b>
<b>3</b>	<b>Stability analysis</b>	<b>4</b>



---

Unité de recherche INRIA Rocquencourt  
Domaine de Voluceau - Rocquencourt - BP 105 - 78153 Le Chesnay Cedex (France)

Unité de recherche INRIA Futurs : Parc Club Orsay Université - ZAC des Vignes  
4, rue Jacques Monod - 91893 ORSAY Cedex (France)

Unité de recherche INRIA Lorraine : LORIA, Technopôle de Nancy-Brabois - Campus scientifique  
615, rue du Jardin Botanique - BP 101 - 54602 Villers-lès-Nancy Cedex (France)

Unité de recherche INRIA Rennes : IRISA, Campus universitaire de Beaulieu - 35042 Rennes Cedex (France)

Unité de recherche INRIA Rhône-Alpes : 655, avenue de l'Europe - 38334 Montbonnot Saint-Ismier (France)

Unité de recherche INRIA Sophia Antipolis : 2004, route des Lucioles - BP 93 - 06902 Sophia Antipolis Cedex (France)

---

Éditeur  
INRIA - Domaine de Voluceau - Rocquencourt, BP 105 - 78153 Le Chesnay Cedex (France)  
<http://www.inria.fr>  
ISSN 0249-6399