



Efficient preconditioning of optimality systems

Kent-Andre Mardal, Bjørn Fredrik Nielsen

► **To cite this version:**

Kent-Andre Mardal, Bjørn Fredrik Nielsen. Efficient preconditioning of optimality systems. International Conference On Preconditioning Techniques For Scientific And Industrial Applications, Preconditioning 2011, May 2011, Bordeaux, France. <inria-00580709>

HAL Id: inria-00580709

<https://hal.inria.fr/inria-00580709>

Submitted on 29 Mar 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Efficient preconditioning of optimality systems

List of authors:

K.-A. Mardal ¹

B. F. Nielsen ²

We propose a rather general preconditioning strategy for the numerical treatment of linear optimality systems (OS) arising in connection with inverse problems for partial differential equations. The preconditioning strategy builds on the framework in [1], which applies to well-posed problems. In the work [2] we explain how the mapping properties of the operators appearing in the OS can be employed to define efficient preconditioners for finite element (FE) approximations of the involved saddle point problem also for problems that are ill-posed. More specifically, it turns out that it is possible to define a scheme such that the number of iterations needed to solve the preconditioned problem is bounded independently of the mesh parameter h , used in the FE discretization, and only increases moderately as the regularization parameter α tends towards zero. In fact, if the associated energy norm is used to define the stopping criterion for the iteration process, then the number of iterations required (in the severely ill-posed case) cannot grow faster than $O((\ln(\alpha))^2)$. This result is obtained by carefully analyzing the properties of the involved operators and thereby revealing the distribution of the eigenvalues of the preconditioned OS. One advantage of our approach is that it only rely on standard elliptic preconditioners based on e.g. multigrid and domain decomposition.

Our theoretical results will be illuminated by a number of numerical experiments.

References

- [1] K.-A. Mardal, and R. Winther. Preconditioning discretizations of systems of partial differential equations, *Numerical Linear Algebra with Applications*, In Press, 2010.
- [2] B. F. Nielsen, and K.-A. Mardal. Efficient preconditioners for optimality systems arising in connection with inverse problems, *SIAM Journal on Control and Optimization*, 48(8), 2010.

¹Simula Research Laboratory and University of Oslo

²Norwegian University of Life Sciences and Simula Research Laboratory