



HAL
open science

A Proposal of Residual Reduction method with preconditioning based on IDR Theorem

Seiji Fujino, Takashi Sekimoto, yusuke Onoue

► **To cite this version:**

Seiji Fujino, Takashi Sekimoto, yusuke Onoue. A Proposal of Residual Reduction method with preconditioning based on IDR Theorem. International Conference On Preconditioning Techniques For Scientific And Industrial Applications, Preconditioning 2011, May 2011, Bordeaux, France. inria-00580787

HAL Id: inria-00580787

<https://hal.inria.fr/inria-00580787>

Submitted on 29 Mar 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A Proposal of Residual Reduction method with preconditioning based on IDR Theorem

List of authors:

Seiji Fujino¹

Takashi Sekimoto² and Yusuke Onoue²

IDR(s) method [4] and extended variants of IDR(s) method [3] based on the IDR Theorem have been proposed one after another. The authors also proposed IDR(s)-based iterative method with iteration matrix of SOR (Successive Over-Relaxation) method in order to accelerate its convergence [2]. In my talk, we propose an algorithm of IDR(s)-based Residual Reduction method using precondition with Eisenstat trick [1]. We refer to IDR(s)-R2 method. We present summary of performance of IDR(s)-R2 method using some preconditions with Eisenstat trick in Table 1. We realize that preconditioned IDR(s)-R2 method outperforms with the conventional iterative methods.

Table 1: Summary of performance of preconditioned IDR(s)-R2 method.

method	precond.	no. of convergence	no. of nonconvergence	no. of fastest case	total (%)
IDR(s)-R2	none	11/18	7/18	0/18	0
	Gauss-Seidel-L	18	0	8	14 (61%)
	Eisenstat-L	17	1	1	
	Eisenstat-UL	17	1	5	
BiCGStab	ILU(0)	15	3	5	5(22%)
BiCGSafe	ILU(0)	15	3	4	4(17%)

References

- [1] Eisenstat, S. C.: Efficient implementation of a class of preconditioned conjugate gradient methods, SIAM J. Sci. Stat. Compute., **2**(1981), 1-4.
- [2] Fujino, S., Sonneveld, P. and van Gijzen, M.B. and Onoue, Y., Application of the IDR Theorem to Stationary Iterative Methods and their Performance Evaluation, The Abstract of SIAM LA09, Monterey (2009).
- [3] Kusakabe, Y., Fujino, S., A proposal of Jacobi method based on extended Induced Dimension Reduction Theorem aimed at high convergence rate, The Proc. of EMAC2009, Adelaide (2009).
- [4] Sonneveld, P., van Gijzen, M.B., IDR(s): a family of simple and fast algorithms for solving large nonsymmetric linear systems, SIAM J. Sci. Comput., **31**(2008), 1035–1062.

¹Research Institute for Information Technology, Kyushu University

²Graduate School of Information Science and Electrical Engineering, Kyushu University