

Cosparse Analysis Modeling

Sangnam Nam, Mike E. Davies, Michael Elad, Rémi Gribonval

► **To cite this version:**

Sangnam Nam, Mike E. Davies, Michael Elad, Rémi Gribonval. Cosparse Analysis Modeling. The 9th International Conference on Sampling Theory and Applications, May 2011, Singapore, Singapore. inria-00591779

HAL Id: inria-00591779

<https://hal.inria.fr/inria-00591779>

Submitted on 16 Sep 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

COSPARSE ANALYSIS MODELING

Sangnam Nam¹

Michael E. Davies²

Michael Elad³

Rémi Gribonval¹

¹ IRISA, INRIA Rennes – Bretagne Atlantique, France

² IDCOM & Joint Research Institute for Signal and Image Processing, Edinburgh University, UK

³ Department of Computer Science, The Technion – Israel Institute of Technology, Israel

ABSTRACT

A ubiquitous problem that has found many applications, from signal processing to machine learning, is to estimate a high-dimensional vector $\mathbf{x}_0 \in \mathbf{R}^d$ from a set of incomplete linear observations $\mathbf{y} = \mathbf{M}\mathbf{x}_0 \in \mathbf{R}^m$. This is an ill-posed problem which admits infinitely many solutions, hence solving it is hopeless unless we can use additional prior knowledge on \mathbf{x}_0 .

The assumption that \mathbf{x}_0 admits a *sparse* representation \mathbf{z}_0 in some *synthesis dictionary* \mathbf{D} is known to be of significant help, and it is now well understood that under incoherence assumptions on the matrix \mathbf{MD} , one can recover vectors \mathbf{x}_0 with sufficiently sparse representations by solving the optimization problem:

$$\hat{\mathbf{x}}_S := \mathbf{D}\hat{\mathbf{z}}; \quad \hat{\mathbf{z}} := \arg \min_{\mathbf{z}} \|\mathbf{z}\|_{\tau} \text{ subject to } \mathbf{y} = \mathbf{MD}\mathbf{z} \quad (1)$$

for $0 \leq \tau \leq 1$.

An alternative to (1) which has been used successfully in practice is to consider the *analysis* ℓ_{τ} -optimization:

$$\hat{\mathbf{x}}_A := \arg \min_{\mathbf{x}} \|\Omega\mathbf{x}\|_{\tau} \text{ subject to } \mathbf{y} = \mathbf{M}\mathbf{x}, \quad (2)$$

where $\Omega : \mathbf{R}^d \rightarrow \mathbf{R}^p$ is an *analysis operator*. Typically the dimensions are $m \leq d \leq p, n$.

The focus of our work is the study of a data model that makes possible to identify a collection of signals \mathbf{x}_0 that can be recovered via the optimization (2). Roughly speaking, in the case of (1), the signals \mathbf{x}_0 that are sparse, in other words, satisfy the *sparse synthesis model*, can be recovered via (1). In the sparse synthesis model, we consider the number of the non-zeros $\|\mathbf{z}\|_0$ of the representation \mathbf{z} of \mathbf{x}_0 (meaning that $\mathbf{x}_0 = \mathbf{D}\mathbf{z}$), and we say that \mathbf{x}_0 is sparse if there is a representation \mathbf{z}_0 of \mathbf{x}_0 with small $\|\mathbf{z}_0\|_0$. To the contrary, in the case of (2), we are more interested in the number of the zeros $p - \|\Omega\mathbf{x}_0\|_0$ of the representation $\Omega\mathbf{x}_0$ of \mathbf{x}_0 . We call the quantity $\ell = p - \|\Omega\mathbf{x}_0\|_0$ the *cosparsity* of \mathbf{x}_0 and say that \mathbf{x}_0 is cosparse, or it satisfies *cosparse analysis model*, if ℓ is large.

For the cosparse analysis model, we have the following uniqueness result:

Proposition 1. *Let Ω be an analysis operator in general position. Then, for almost all \mathbf{M} (with respect to the Lebesgue measure), a necessary and sufficient condition for (2) with $\tau = 0$ to have a unique minimum is*

$$m \geq 2(d - \ell). \quad (3)$$

The proposition characterizes the collection of signals that can be recovered from (2) for the generic case. We also observe that by comparing with the uniqueness result for the sparse synthesis model, again in generic cases, $d - \ell$ is playing the role of the sparsity $k = \|\mathbf{z}_0\|_0$.

In the sparse synthesis model, armed with the fact that \mathbf{x}_0 has a sparse representation, one may try to recover/approximate \mathbf{x}_0 by greedily selecting atoms from \mathbf{MD} and matching the observation \mathbf{y} . The Orthogonal Matching Pursuit (OMP) is an example of such approaches. Similarly, we can consider a greedy algorithm as an alternative to (2) in the cosparse analysis model. As such an algorithm, we propose the Greedy Analysis Pursuit (GAP). In this algorithm, contrary to the greedy algorithms for the synthesis model, we try to identify the rows of Ω that correspond to the zeros of $\Omega\mathbf{x}_0$. Moreover, again contrary to the typical greedy approach, GAP greedily—perhaps, generously—removes a row that is likely not to correspond the zeros from a collection of candidate rows that may do. This way, instead of building the support of \mathbf{z}_0 by growing the size of the support as is done in, for example, OMP, we are carving out unwanted rows in order to obtain the correct cosupport of \mathbf{x}_0 , i.e., the set of the indices that correspond to the zeros of $\Omega\mathbf{x}_0$.

Finally, we run a synthetic experiment to demonstrate the effectiveness of the proposed algorithm, GAP. Interestingly, we observe from the phase transition diagrams obtained from the experiment that GAP performs better than the analysis ℓ_1 -minimization.

Keywords— Sparse Representation, Inverse Problems, Algorithms, Cosparse Analysis Model

1. REFERENCES

- [1] T. Blumensath and M. E. Davies. Sampling theorems for signals from the union of finite-dimensional linear subspaces. *IEEE Transactions on Information Theory*, 55(4):1872–1882, 2009.

The authors acknowledge the support by the European Community's FP7-FET program, SMALL project, under grant agreement no. 225913.

- [2] E. J. Candès, Y. C. Eldar, D. Needell, and Y. Ma. Compressed sensing with coherent and redundant dictionaries. Technical Report <http://arxiv.org/abs/1005.2613v1>, arXiv, 2010.
- [3] D.L. Donoho and M. Elad. Optimally sparse representation in general (nonorthogonal) dictionaries via ℓ^1 minimization. *Proc. Nat. Aca. Sci.*, 100(5):2197–2202, March 2003.
- [4] M. Elad, P. Milanfar, and R. Rubinstein. Analysis versus synthesis in signal priors. *Inverse Problems*, 23(3):947–968, June 2007.
- [5] R. Gribonval and M. Nielsen. Sparse representations in unions of bases. *IEEE Trans. Inform. Theory*, 49(12):3320–3325, December 2003.
- [6] Y. M. Lu and M. N. Do. Sampling signals from a union of subspaces. *IEEE Signal Processing Magazine*, pages 41–47, mar 2008.
- [7] J. Portilla. Image restoration through 10 analysis-based sparse optimization in tight frames. *Proceedings of the 16th IEEE International Conference on Image Processing*, pages 3865–3868, 2009.
- [8] I. W. Selesnick and M. A. T. Figueiredo. Signal restoration with overcomplete wavelet transforms: Comparison of analysis and synthesis priors. *In Proceedings of SPIE*, 7446 (Wavelets XIII), August 2009.